

(SUBMIT IN TRIPLICATE)

Approval expires 11-30-49.
and Office Salt Lake
Lease No. 045051-A

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Clay Basin Dagget Utah (County or Subdivision) Clay Basin Dagget Utah (County or Subdivision) (State names of and expected depths to objective sands; show sizes, weights, and iongths of proposed casings; indicate mudding jobs, ceme ing points, and all other important proposed work) A string of tubing was run and set in this well as follow 77 Jts. 5447'8" Gross 5418'2" Net of 2" - 4.60# - 10 Thd. UE Tubing 1 Jt 25'9" " 25'7" " 2½"- 6.40# - 10 Thd. UE Tubing 1 Jt 25'9" " 25'7" " 2½"- 6.40# - 10 Thd. UE Tubing 6 5473'5" " 5443'9" " Landed on minderliter tubing head at 5438'9" - 5' above to round. A 5'6" perforated anchor, which is included in the above ally, was used on the bottom of the tubing. Tubing set 3' from be finde. A 5'6" tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing of completed febr. 18, 1938 I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN TUSE SUPPLY CO. BOX 932 Address Nock Springs. "Yo.	
Notice of intention to test water shut-off	
NOTICE OF INTENTION TO RE-ORILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE. SUBSEQUENT REPORT OF REDRILLING OR REPAIR. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO DEADNOON WELL NOTICE OF INTENTION TO BEADNOON WELL NOTICE OF INTENTION TO SHOOT ALTER CASING. R. D. MUTPHY #1 **COCK SOTIORS . MYO. Febr. 21 . 19.2** Well No. 1 is located \$20.9 ft. from No. Notice on Other Batta R. D. MUTPHY #1 **Well No. 1 is located \$20.9 ft. from No. Notice on Other Batta R. D. MUTPHY #1 Well No. 1 is located \$20.9 ft. from No. Notice on Other Batta R. D. MUTPHY #1 Well No. 1 is located \$20.9 ft. from No. Notice on Other Batta R. D. MUTPHY #1 Well No. 1 is located \$20.9 ft. from No. Notice on Other Batta R. D. MUTPHY #1 Well No. 1 is located \$20.9 ft. from No. Notice on Other Batta R. D. MUTPHY #1 **Well No. 1 is located \$20.9 ft. from No. Notice of County of Subdivision (State or Territory) The elevation of the derrick floor above sea level is \$4.91 ft. **DETAILS OF WORK State names of and expected depths to objective sands show sizes, weight, and lengths of proposed casings, indicate mudding John. comming points, and all other important proposed works) A strings of tubing was set in a this well as follow A strings of tubing was set in this well as follow Ty Jts. \$447'8" Gross \$5418'2" Het of 2" - 4.60 ft. 10 Thd. UE Tubing **SATIOR** **SATIOR** **DETAILS OF WORK State or Territory) The elevation of the derrick floor above sea level is \$6491 ft. **DETAILS OF WORK State or Territory) **The elevation of the derrick floor above sea level is \$6491 ft. **DETAILS OF WORK State or Territory) **The elevation of the derrick floor above sea level is \$6491 ft. **DETAILS OF WORK State or Territory) **The elevation o	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE. NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO BARNDON WELL. NOTICE OF TUDING "cell X (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) R. D. MUTPHY #1	
NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL Motice of Tubing well x (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA) R. D. Murphy #1 **Rock Sorings dyo. Febr. 21 19.2* Well No. 1 is located 0.09 ft. from \(\frac{N}{2} \) line and 255 ft. from \(\frac{E}{2} \) line of sec. 22 (Well No. 1 is located 0.09 ft. from \(\frac{N}{2} \) line and 255 ft. from \(\frac{E}{2} \) line of sec. 22 (Well No. 1 is located 0.09 ft. from \(\frac{N}{2} \) line and 255 ft. from \(\frac{E}{2} \) line of sec. 22 (Well No. 1 is located 0.09 ft. from \(\frac{N}{2} \) line and 255 ft. from \(\frac{E}{2} \) line of sec. 22 (Well No. 1 is located 0.09 ft. from \(\frac{N}{2} \) (Range) (Meridian) (Passin	
Notice of Tubics (ell knows by check mark nature of Report, Notice of Tubics (ell knows by check mark nature of Report, Notice of Other Data) R. D. Murphy #1 Rock Springs, #yo. Febr. 21. 19.2 Well No. 1 is located 90.9 ft. from N line and 20.5 ft. from Elline of sec. 22. Well No. 2 S N. 24 E. Grado (Twp) (Clause) (Meridian) Clay Basin Dagget Utah (County or Subdivision) (State of Territory) The elevation of the derrick floor above sea level is 6491 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding Jobs, come in the points, and all either important proposed works A string of tubing was run and set in this well as follow A string of tubing was run and set in this well as follow To Jts. 5447'8 Gross 5418'2" Ret of 2" - 4.60% - 10 Thd. UE Tubic 25'9" " 25'7" " 25'8 - 5.40% - 10 Thd. UE Tubic 11 Jt 25'9" " 5443'9" " Landed on hinderliter tubing head at 5438'9" - 5' above to cound. A 5'6" perforated anchor, which is included in the above ally, was used on the bottom of the tubing. Tubing set 3' from be follow, as the tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing of completed Febr. 18, 1938 I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company MOUNTAIN TUSL SUPPLY CO. BOX 932 Address. Rock Springs. "yo. Pistrict Engr.	
(Indicate Above by Check Mark Nature of Report, Notice or Other Data) R. D. Murphy #1 **Rock Sorings, dyo. Febr. 21, 19.2 Well No. 1 is located 0.69 ft. from No. 1 line and 2.55 ft. from E. line of sec. 22 **SWANNA Sec. 22 **SN. 24 E. (R Sec. and Sec. No.) **Clay Basin	
Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from [N] line of sec. 22 Well No. 1 is located 069 ft. from [N] line and 265 ft. from 06 ft. line of sec. 22 Well No. 1 is located 069 ft. from 20 line of sec. 22 Well No. 1 is located 069 ft. from 20 line of sec. 22 Well No. 1 is located 069 ft. from 20 line of sec. 22 Well No. 1 is located 069 ft. from 20 line of sec. 22 Well No. 1 is located 069 ft. from 20 line of sec. 22 Well No. 1 is located 069 ft. from 20 line of tubing was used on from 25 line of sec. 22 Well No. 1 is located 069 ft. from 25 line of sec. 22 Well No. 1 is located 069 ft. from 26 line of sec. 22 Well No. 1 is located 069 ft. from 26 line of sec. 22 Well No. 1 is located 069 ft. from 26 line of sec. 22 line of sec. 22 Well No. 1 is located 069 ft. ft. from 26 line of sec. 22 line of	
Well No. 1 is located 069 ft. from No. 1 is located 069 ft. from No. 25 ft. from No. 1 is located 069 ft. from No. 25 ft. from No. 25 ft. from No. 26 ft. from No. 26 ft. from No. 26 ft. from No. 27 No. 24 ft. (Need and See No.) (Twp.) (Clay Besin Degree Of the derick floor above sea level is 6491 ft. DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) A string of tubing was run and set in this well as follow 1 ft. 25 ft. 27 ft. 25 ft. 27 ft. 25 ft. 26 ft. 10 ft. 27 ft. 25 ft. 27	
Well No. 1 is located 0.69 ft. from No. 25 ft. from William of sec. 22	
Clay Basin Dagget Utah (County or Subdivision) (State or Territory) The elevation of the derick floor above sea level is 6491. ft. DETAILS OF WORK (State names of and expected depths to objective and set with search important proposed work) A string of tubing was run and set in this well as follow 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	8
Clay Basin Dagget Utah (County or Subdivision) (State or Territory) The elevation of the derick floor above sea level is 6491 ft. DETAILS OF WORK (State names of and expected depths to objective seands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme ing points, and all other important proposed work) A string of tubing was run and set in this well as follow A string of tubing was run and set in this well as follow 1	
Clay Basin Dagget Utah (County or Subdivision) (State or Territory) The elevation of the derick floor above sea level is 6491 ft. DETAILS OF WORK (State names of and expected depths to objective seands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ceme ing points, and all other important proposed work) A string of tubing was run and set in this well as follow 77 Jts. 5447'8" Gross 5418'2" Net of 2" - 4.50% - 10 Thd. UE Tubing 1 Jt 25'9" 25'7" " 2½"-6.40% - 10 Thd. UE Tubing 5473'5" " 5443'9" " Landed on minderliter tubing head at 5438'9" - 5' above to round. A 5'6" perforated anchor, which is included in the above ally, was used on the bottom of the tubing. Tubing set 3' from by findle. A joint of 2-1/2' tubing was used on top to land this strict tubing, as the tubing head was for 2-1/2" tubing. A steel swag imple was used to connect the 2-1/2" to the 2" tubing. Tubing of completed Febr. 18, 1938 I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company MOUNTAIN TUYL SUPPLY CO. BOX 932 Address. Kook Springs, "yo. Plant of Engr. District Engr. By C. A. "etzler	
(County or Subdivision) (County or Subdivisio	
(County or Subdivision) (County or Subdivisio	
DETAILS OF WORK (State names of and expected depths to objective and as show size, weights, and lengths of proposed casings, indicate mudding jobs, come ing points, and all other important proposed work) A string of tubing was run and set in this well as follow 77 Jts. 5447'8" Gross 5418'2" Net of 2" - 4.60 \(\pi - 10\) Thd. UE Tubing 1 Jt \(\frac{25'9"}{25'9"} \) " \(\frac{25'7"}{25'7"} \) " \(2\frac{1}{2}" - 6.40 \) - 10 Thd. UE Tubing 1 Jt \(\frac{26'9"}{25'9"} \) " \(\frac{5443'9"}{5443'9"} \) " Landed on hinderliter tubing head at 5438'9" - 5' above the cound. A 5'6" perforated anchor, which is included in the above ally, was used on the bottom of the tubing. Tubing set 3' from the final point of 2-1/2" tubing was used on top to land this strict tubing, as the tubing head was for 2-1/2" tubing. A steel swag inple was used to connect the 2-1/2" to the 2" tubing. Tubing of completed rebr. 18, 1938 I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. Dox 932 Address Rock Springs ''yo. Poroved Feb. 25, 1938 R. D. Ferguson By C. T. "etzler District Engr.	-
A string of tubing was run and serviced depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemering points, and all other important proposed work) A string of tubing was run and set in this well as follow 77 Jts. 5447'8" Gross 5418'2" Net of 2" - 4.60% - 10 Thd. UE Tubing 1 Jt	
A string of tubing was run and set in this well as follow 77 Jts. 5447'8" Gross 5418'2" Net of 2" - 4.60# - 10 Thd. UE Tubing 1 Jt	
A string of tubing was run and set in this well as follow 77 Jts. 5447'8" Gross 5418'2" Net of 2" - 4.60# - 10 Thd. UE Tubing 1 Jt	nt-
The state of the s	
Landed on Hinderliter tubing head at 5438'9" - 5' above to round. A 5'6" perforated anchor, which is included in the above ally, was used on the bottom of the tubing. Tubing set 5' from be hole. A joint of 2-1/2" tubing was used on top to land this strest tubing, as the tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing or completed rebr. 18, 1938 I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. BOX 932 Address Rock Sorings, Myo. Oproved Feb. 25, 1938 R. D. Ferguson By C. M. Metzler	ng Lng
round. A 5'6" perforated anchor, which is included in the above ally, was used on the bottom of the tubing. Tubing set 3' from be finde. A joint of 2-1/2" tubing was used on top to land this stress tubing, as the tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing opposed we have approved in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, "yo. Sproved Feb. 25, 1938 R. D. Ferguson District Engr. By C. M. Hetzler	
ally, was used on the bottom of the tubing. Tubing set 3' from be hole. A joint of 2-1/2' tubing was used on top to land this stresh tubing, as the tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing opposed be broad approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN TUBL SUPPLY CO. BOX 932 Address Rock Springs, Myo. Oproved Beb. 25, 1938 R. D. Ferguson District Engr.	the ·
f hole. A joint of 2-1/2" tubing was used on top to land this stresh tubing, as the tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing opposed rebr. 18, 1938 I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, Myo. poroved reb. 25, 1938 R. D. Ferguson District Engr.	ottom
f tubing, as the tubing head was for 2-1/2" tubing. A steel swag ipple was used to connect the 2-1/2" to the 2" tubing. Tubing or ompleted rebr. 18, 1938 I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, "yo. oproved reb. 25, 1938 R. D. Ferguson District Engr.	ing
ipple was used to connect the 2-1/2" to the 2" tubing. Tubing operations of completed febr. 18, 1938 I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, Myo. poroved feb. 25, 1938 R. D. Ferguson District Engr.	.e
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. BOX 932 Address Rock Springs, Myo. oproved Feb. 25, 1938 R. D. Ferguson District Engr.	erati
I understand that this plan of work must receive approval in writing by the Goological Survey before operations may be commenced. Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, Wyo. oproved Feb. 25, 1938 R. D. Ferguson By C. A. Hetzler District Engr.	
Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, "yo. Sproved Feb. 25, 1938 R. D. Ferguson By C. A. Hetzler District Engr.	
Company MOUNTAIN FUEL SUPPLY CO. Box 932 Address Rock Springs, Myo. oproved Feb. 25, 1938 R. D. Ferguson By C. M. Hetzler District Engr.	
Address Rock Springs, Myo. oproved Feb. 25, 1938 R. D. Ferguson District Engr.	
pproved Feb. 25, 1938 R. D. Ferguson District Engr. By C. A. Hetzler	
oproved Feb. 25, 1938 R. D. Ferguson District Engr. By C. A. Hetzler	
District Engr.	
District Engr.	
- Casper wyo. Title Vice President	
	· .
T J V	

ity Daggett

		<i>(</i>	TILLD &	PADOUATORI	KEPURI Ç	ity Dag	gett
	y No. 1 Basin		Stratigraph	Sec. SK	NW 22 of Sand F	T 3 N	R 24 E
Date Well Comp Date of Sample Sample Taken b Well Owned by Address Lab. Sample No	ing 11/25 by E.M. T Mounts Rock S 3050	11 1927 3/41 Tignor & Ain Fuel Aprings.	Daily c Sample R,H,Espac Supply Co .Wyoming . Date Anal	apacity of Cylinder No Chaddress cmpany	Well 3.1/4 439 U.S.B.M. Le	Pressure in Cy ramie, Wyomir	linder 200
<u>Orsat Anal. by</u> Orsat Anal.		ineeLer		Fract	. Dist. by .	*************	
oreat Allar.	CO ₂					Total	He. Anal.
	0.4%	0.2%	87.9%	11.2%	0.3%	100%	0.04%
Fract. Dist.	CO ₂	0 2	CH 4	C ₂ H ₆	C ₃ H ₈	$C_4H_{10} + N_2$	& He. Total

Remarks: *Upper 5373-5375, lower 5395

Sampled at meter house, well producing. Gas had gone thru separator for distillate removal. Well produces about 1 1/2 MM at 610# wellhead pressure.

9-546-a (August, 1932)

DEPARTMENT OF THE INSTRICT



Geological Survey Laboratory - Midwest, Wyoming

INF EMATION TO BE FURRISHED WITH FACE SANTLE OF CAS

Varks on container (Filled by Chemi. Source of SAMPLE:	st
and the control of th	
Clay Easin, Utah	•
(Serial number)	
Operator Chio Cil Company Operator's Address Caspor Tyoming	
Woll No. Robt. D. Murchy. 1/4 Sec21 T Z.W. R R M M.	•
Sample taken by	•
If known, name of sand (or formation) from which this sample is produced Pekota	•
I a state) with the so state and the state of the state o	
Depth to top of sand	•
Topth well drilled Present depth	
ACPUI WILL GRILLEG decessors sees escessors of POSCIL GOPUI assessors escessors escessors	•
Depths(if known) where water encountered	•
Depth at which water string is landed, comented, midded	•
METHOD OF SAMPLING:	
Please place where sample was obtaine (sump hole, lend line, flow tank, bailer, etc.)	
Mothod of production (flowing, pumping, air, etc.)	▶
요하는 사람이라는 어린 그 이자 얼굴에도 돌고했다. 중요한 사람들은 생활하는 바람이 하는 사람이 모든 사람이 없다.	11. . :
Initial Production: Present Production:	
Barrels oil	
Barrels Water Barrels Water secusions	
Gas Volume Gas Volume	
Rock Pressure Rock Pressure	
REASON FOR ANALYSTS:	
(1) Puture reference	
(3) Corrolation ************************************	
(4) ************************************)

NOTE: A sample for analysis is of no value unless accompanied by above information. Complete information on this form is to be attached to each sample container; otherwise sample will be disregarded. He sure to seal or tightly cork all containers immediately after sampling and label all samples so that there will to no confusion.

GAS AMALYSIS

Condition o	f sample	* 4 4 * * * * * * * *	5040464543	Labor	ratory No	
Analysis by	· · · · · · · · · · · · · · · · · · ·	Crawford	g w o u y o a	t . Widwest.	. Wyoming	. Late . 9-16-35

ORSAT AMALYSIS

Carbon dioxido (CO₂) 0.0%

Oxygon (O₂) 72.5%

Mothano (CM₁) 72.5%

Ethano (C₂N₆) and higher 13.0%

Nitrogen (N₂) by difference ... 11:2%

Specific Gravity (Calculated) 689

Calculated Gross B. T. U. per cu. ft. at 60° F. and 15.025 lbs. per sq. inch preceure 980

HYDROGEN SULPHID BY TUIVILER METHOD.

Grains of hydrogen sulphide per 100 cu. ft. of gas at 60 F. and 15.025 lbs. per sq. in.

Percentage of hydrogon sulphide at 60° F. and 15.025 lbs. per sq. in.......

HEATIEG VALUE BY SARGENT CAS CALGRINGTER

B. T. U. per eu. ft. at 60° F. and 15.025 lbs. per eq. inch. pressure as determined by Sargent gas calcrimoters

Gross 1172 Not 1041 1021 2 30 " Hercey

Remarks and conclusions:



l Office .	Salt	Lalto.
Serial Number 🖟		<u> </u>
Lease or Permit	,	i.coco

SUNDRY NOTICES AND REPORTS ON WELLS

. *		· · · · · · · · · · · · · · · · · · ·				
	NOTICE OF INTENTION TO DE	RILL	SUBSEQUENT RECORD OF S	HOOTING		
-	NOTICE OF INTENTION TO CH	1	RECORD OF PERFORATING			
	NOTICE OF DATE FOR TEST O	ļ	NOTICE OF INTENTION TO P		TER CASING.	
	REPORT ON RESULT OF TEST	1	NOTICE OF INTENTION TO A			
	NOTICE OF INTENTION TO RE-	ORILL OR REPAIR WELL	SUBSEQUENT REPORT OF AB	ANDONMENT		
	NOTICE OF INTENTION TO SHO	от	SUPPLEMENTARY WELL HIST			
· ·	(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR C	THER DATA)		
R D	NURPEN (1		Capper, Sycains, 30	rtakar Id. 15	, 19	
	Following is a {	notice of intention to do report of work done	work on land under per	mit described as	follows:	
	Ulch	Degget	i de	Clay Lastin	ea Ash	
1	(State or Territory)		(County or Subdivision)		ield)	•
V	Vell No	1772 Eno 12	73N - RM		Singled's Solt L	odo
	•	(1/4 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	
T	The well is located 20	69 ft S of 1 line	and 265 ft. E of E	line of sec.	p. A.	
. Τ	The elevation of the der	rick floor above sea leve	l is <u>6437</u> ft.			
		DETAILS O	F PLAN OF WORK			
(S	itate names of and expected depth	s to objective sands; show sizes, wei all other im	ghts, and lengths of proposed casings portant proposed work.)	; indicate mudding jobs,	cementing points, and	
This	well was employ	of by the Producers	and Weliners Corps	ration at a 1	istal dopti	
of 5	645° on April 6, 1	lerr. Printler Sin	d, and well good fo	x 5,276,000 c	n ft of gus.	
Keori	a by the PaR as T	hell \$2". The leas	und and lies has a	teen assigned	to the Bounts	ain
Puel	Supply Co., who s	illi operate the pr	sperty. The Hounts	in that Suppl	y Co. did not	
tako	en old abandoned	hale known by the	rea as "Not1 61" in	to its record	s, but is et t	Lto
pres	guilling eath the	a soll known to th	a Rountain Puol Sup	oly Co. es %	urply fr.	**
Ko wi	ish paratenion to	take the FAR's #2 :	into our records es	our Murphy	A Page 1	
A //	Approved Doc 2	(Date)	Company By	intels. Type s	upply Co.	<u> </u>
	Title	GEOLOGICAL SURVEY		President (100	
	Address Co	an Drink	Address	per, Woming		
	NOTE-Reports on this form	to be submitted in triplicate to the		Government print	TING OFFICE 6-7053	٠,

Mountain Fuel Supply To.		ran	n	The state of the s	W r	i No	
I.P. G. 3.276 P. C. a. i.P. 2110 S							
### 22 Drilling Commerced Sept. 10, 1925 Completed April 6, 1927 Total Depth 5445 Semilar 5445 Semilar 5425 Semilar 54			and the second s				
Test Part Samb							l
######################################		Drilling Commenced	36hr. 10,				
	22		W	7	Total Depth	5445	يتقلون ودعيته مدالتين برنواجين دي
150		Remarks:	·	· ·			
15th 70f 901 8 15mil Now 20 90f 9518 1anded at 1041 8		Sands			4. A		
185" 70# 901 8" Landed at 9061 "; 185" 50# 1873 8" indeed at 18507" Cemonted 225 sacis; 10" 48# 2859 4" landed at 283010" commontad 25 sacks; 62" 28# 476015" landed at 483010" commontad 25 sacks; 63" 28# 476015" landed at 4830410" commonted 25 sacks; 63" 28# 476015" landed at 534411" commonted 90 sacks. FREMATION REDONIO From To Gravel and rock 0 40 Shale 5375 538 Shale - dark 40 250 Shale 5375 538 Shale - dark 40 250 Shale 5375 538 Shale sacils - gray, 250 Shale 5382 538 Shale - gray 325 Shale 5382 538 Shale - gray 325 Shale 5382 538 Shale, gray 344 340 345 Shale, gray 345 340 345 Shale, gray 345 340 345 Shale, gray 345 340 345 Shale, gray 340 345 Shale, gray 340 345 Shale, shalls, gray 600 665 Shale, blue 665 705 Shale, sandy, gray 795 1000 Shale, sandy gray 1150 1306 Shale, sandy gray 1150 1306 Shale, sandy gray 1150 1306 Shale, gray 1220 1370 Shale, gray 1320 1370 Shale, gray 1320 1370 Shale, gray 1460 1680 Shale, gray 1500 1680 Shale, sandy blue 1600 1680 Shale, sandy 1100 1870 Shale, sandy 1100 1100 Shale, sa		· · · · · · · · · · · · · · · · · · ·	90# 9518"	Tanded et 1	041 8".	- Allert Haller and Allert and Al	
Comented 225 sacks; 10" 45# 2059' 4" Landed at 2850'10" comented 25 sacks; 6% 25# 4054' 4055'0" landed at 4010'3" comented 25 sacks; 6% 25# 25# 4760'5" la 4700'5"; 4% 15# 15# 5592'2" landed at 8344'11" comented 90 sacks; 6% 25# 25# 4760'5" la 4700'5"; 4%" 15# 5592'2" landed at 8344'11" comented 90 sacks; 6% 25# 25# 4760'5" la 4700'5"; 4%" 15# 5592'2" landed at 8344'11" comented 90 sacks; 6% 25# 25# 4760'5" landed at 8344'11" comented 90 sacks; 6% 25# 25# 4760'5" landed at 8344'11" comented 90 sacks; 6% 25# 25# 25# 25# 25# 25# 25# 25# 25# 25#	15% 70# 9011	8" Landed at	896! 4":	12a'' 50# 187	31 8" Lan	ded at 18	3501711
### Topin	Comented 225	sacks: 10" 45	# 28591 4"	landed at 2	830'10" c	emented 2	25 sacl
Formation Record Formation	8位 ¹¹ 32# 40531	O" landed at	4010'3" ce	mented 25 sa	.cks; $6\frac{1}{2}$ "	26# 47 60!	5" lar
Grayel and rook 0 40 Shale - dark 40 250 Shale & shells - gray, show of gas at 514' 250 320 Shale & show of gas at 514' 250 320 Shale & show of gas at 514' 250 320 Shale & 5302 538! Shale - gray 325 340 Shale , gray 325 340 Shale , gray 348 395 Shale, gray 395 540 Shale, gray 395 540 Shale, gray 395 540 Shale & shelly, gray 600 665 Shale, blue 665 795 Shale, sandy, gray 795 1000 Sand, fine gray 1000 1055 Shale, sandy gray 1055 1100 Shale, sandy gray 1150 1306 Shale, sandy gray 1150 1306 Shale, gray 1000 Shale, gray 5333 Shale, gray 5333 Shale, gray 5333 Shale, gray 5333 Shale, gray 5332 Shale	l .	,	anded at 5	344'11" come	nted 90 s	acks.	
Gravel and rook	FORM	ATION RECORD			FORMATION	RECORD	
Shale - dark 40 25		From	To	e vive se.		From	To
Shale - dark 40 25	Gravel and rock	0	40	Shola		. Eane	5700
Shale & shells - gray 320 320 5hell 320 325 5hell 320 325 340 5hell - gray 325 340 5hell - gray 325 340 5hale gray 325 340 5hale gray 345 398 5hale gray 345 398 540 5hale gray 395 540 5hale gray 395 540 5hale gray 395 540 5hale gray 540 665 5hale shells gray 600 665 5hale shells gray 795 1000 5and, fine gray 1000 1050 5hale sandy gray 795 1000 5hale sandy gray 1500 1300 5hale gray 1000 1300 5hale gray 1320 1370 3hale gray 1460 1462 3hale blue 1370 1460 3hale shad sandy blue 1500 1580 3hale shad shad 1460 1462 3hale blue 1740 1875 3880 388	1		250)			
Show of gas at 314' 250 320 325 Shall - gray 325 340 345							
Shell	show of gas a	314 250	320		- 088		
Shell - gray 325 340 345 Shell show gas at 344 345 Shell gray 345 395 Shale gray 345 395 Shale gray 345 395 Shale - gray 346 600 Shele - gray 540 600 Shele - gray 795 1000 555 Shele gray 1000 1055 Shele gray 1005 1100 Shele gray 1005 1100 Shele gray 1150 1305 Shele gray 1150 1305 Shele gray 1320 1370 1460 Shele gray 1320 1370 1460 Shele 1370 1460 Shele 1370 1460 Shele 1462 1500 Shele 1580 1580 Shele 1580 1580 Shele 1580 1580 Shele 1580 1680 Shele sandy blue 1710 1740 Shele sandy gray 1880 1910 Shele sandy gray 1880 1910 Shele sandy blue 3050 3250 Shele calcareous sandy shele 4550 4250 Shele calcareous sandy shele 4550 4600 Shele calcareous sandy shele 4640 4850 Shele calcareous blue 4550 4600 Shele calcareous blue 4640 4850 Shele calcareous blue 4640 4850 Shele calcareous blue 4640 4850 Shele calcareous blue 4650 4855 Shele sandy shard sandy sandy sandy shard sandy sandy sandy shard sandy sandy shard sandy	Shell			Sandy shale	e '546		
Shell, show gas at 344' 340	Shale - gray	325	340				
Shale - gray 540 600 655 Shale, blue 665 795 Shale, sandy, gray 795 1000 Sand, fine gray 1000 1055 Shale, sandy, gray 1055 1100 Shale, sandy gray 1055 1100 Shale, sandy gray 1150 1505 Shale, blue 1305 1320 Shale, gray 1320 1370 Shale, blue 1370 1460 Shall, hard 1460 1462 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, sandy, blue 1580 1680 Shale, blue 1580 1680 Shale, blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, blue 4350 4650 Shale, calcareous, black 4850 4855 Shale, sandy, very calcareous, black 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Scand, gray 5353 5343 Scand, gray 5352 5373 Shale, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373 Scand - Approx. 2 K.	Shell, show gas	at 344! 340	345		. *	, 0220	0110
Shale - gray 540 600 655 Shale, blue 665 795 Shale, sandy, gray 795 1000 Sand, fine gray 1000 1055 Shale, sandy, gray 1055 1100 Shale, sandy gray 1055 1100 Shale, sandy gray 1150 1505 Shale, blue 1305 1320 Shale, gray 1320 1370 Shale, blue 1370 1460 Shall, hard 1460 1462 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, sandy, blue 1580 1680 Shale, blue 1580 1680 Shale, blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, blue 4350 4650 Shale, calcareous, black 4850 4855 Shale, sandy, very calcareous, black 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Scand, gray 5353 5343 Scand, gray 5352 5373 Shale, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373 Scand - Approx. 2 K.	Shale, gray	345	395 -		. •	•	
Shale - gray 540 600 655 Shale, blue 665 795 Shale, sandy, gray 795 1000 Sand, fine gray 1000 1055 Shale, sandy, gray 1055 1100 Shale, sandy gray 1055 1100 Shale, sandy gray 1150 1505 Shale, blue 1305 1320 Shale, gray 1320 1370 Shale, blue 1370 1460 Shall, hard 1460 1462 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, sandy, blue 1580 1680 Shale, blue 1580 1680 Shale, blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, blue 4350 4650 Shale, calcareous, black 4850 4855 Shale, sandy, very calcareous, black 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Scand, gray 5353 5343 Scand, gray 5352 5373 Shale, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373 Scand - Approx. 2 K.	Shale, shelly, 8	ray 395	540				
Shale, blue	Shale - gray	540	· ·			* *	
hard 1100 1150 1305 Shale, sandy gray 1150 1305 Shale, blue 1305 1320 Shale, gray 1320 1370 Shale, blue 1370 1460 Shale, blue 1462 1500 Shale, blue 1462 1500 Shale, blue 1500 1580 Shale, blue 1560 1680 Shale, blue 1560 1680 Shale, blue 1710 1740 Shale, blue 1710 1740 Shale, blue 1710 1740 Shale, blue 1740 1875 1880 Shale, sandy blue 1710 1305 1306 13	Shale & shells,	gray 600	665		* * *	¥.	
hard 1100 1150 1305 Shale, sandy gray 1150 1305 Shale, blue 1305 1320 Shale, gray 1330 1370 Shale, blue 1370 1460 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, sandy, blue 1500 1580 Shale, sandy blue 1580 1680 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 1880 Shale, blue 1740 1875 1880 Shale, sandy gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4640 4650 Shale, calcareous, blue 4640 4650 Shale, calcareous, blue 4640 4850 Shale, sandy 5323 5333 5343 5349 5349 5349 5349 5352 5343 5349 5349 5352 5348 5349 5361 5349 5352 5343 5349 5361 5349 5352 5361 5349 5362 5361 5349 5362 5362 5362 5362 5362 5362 5362 5362 5362 5362 5362 536	Shale, blue	665	795			***	
hard 1100 1150 1305 Shale, sandy gray 1150 1305 Shale, blue 1305 1320 Shale, gray 1330 1370 Shale, blue 1370 1460 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, sandy, blue 1500 1580 Shale, sandy blue 1580 1680 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 1880 Shale, blue 1740 1875 1880 Shale, sandy gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4640 4650 Shale, calcareous, blue 4640 4650 Shale, calcareous, blue 4640 4850 Shale, sandy 5323 5333 5343 5349 5349 5349 5349 5352 5343 5349 5349 5352 5348 5349 5361 5349 5352 5343 5349 5361 5349 5352 5361 5349 5362 5361 5349 5362 5362 5362 5362 5362 5362 5362 5362 5362 5362 5362 536	Shale, sandy, gr	ray 795	1000			* 2 *	
hard 1100 1150 1305 Shale, sandy gray 1150 1305 Shale, blue 1305 1320 Shale, gray 1320 1370 Shale, blue 1370 1460 Shale, blue 1462 1500 Shale, blue 1462 1500 Shale, blue 1500 1580 Shale, blue 1560 1680 Shale, blue 1560 1680 Shale, blue 1710 1740 Shale, blue 1710 1740 Shale, blue 1710 1740 Shale, blue 1740 1875 1880 Shale, sandy blue 1710 1305 1306 13	Sand, line gray	1000	1055				
hard 1100 1150 1305 Shale, sandy gray 1150 1305 Shale, blue 1305 1320 Shale, gray 1330 1370 Shale, blue 1370 1460 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, sandy, blue 1500 1580 Shale, sandy blue 1580 1680 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 1880 Shale, blue 1740 1875 1880 Shale, sandy gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4640 4650 Shale, calcareous, blue 4640 4650 Shale, calcareous, blue 4640 4850 Shale, sandy 5323 5333 5343 5349 5349 5349 5349 5352 5343 5349 5349 5352 5348 5349 5361 5349 5352 5343 5349 5361 5349 5352 5361 5349 5362 5361 5349 5362 5362 5362 5362 5362 5362 5362 5362 5362 5362 5362 536	Shale, gray	1055	1100				
Shale, sandy gray 1150 1305 Shale, blue 1305 1320 Shale, blue 1370 1460 Shell, hard 1460 1462 Shell, hard 1460 1580 Shale, sandy, blue 1500 1580 Shale, blue 1580 1680 Shale, blue 1580 1710 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 175 Sand, dark 1875 1880 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, sandy, blue 3050 3250 Shale, sandy, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4600 4640 Shale, calcareous, blue 4600 4650 Shale, calcareous, blue 4600 4650 Shale, calcareous, blue 4650 4855 Chloroform test showed little oil Shale, calcareous, blue, sandy, calcareous, blue 4655 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Cool, show of gas 5343 5349 Shel, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373	Shale, sandy, gr						
Shale, blue 1305 1320 Shale, gray 1320 1370 Shale, blue 1370 1460 Shell, hard 1460 1462 Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, blue 1580 1680 Shale, blue 1580 1680 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy, gray 1880 1910 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, sandy, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, blue 4250 4350 Shale, calcareous, sandy, blue 4600 Shale, calcareous, blue 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very addy calcareous, black 4850 4855 Chloroform test showed 11ttle oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell, sandy, gray 5352 5573 Shale, sandy, gray 5352 5573						3	
Shale, gray 1320 1370 1360 Shale, blue 1370 1460 Shell, hard 1462 1500 Shale, blue 1580 1580 Shale, blue 1580 1580 Shale, sandy, blue 1580 1680 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 1880 Shale, sandy blue 1710 3050 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, blue 3050 3250 Shale, calcareous, sandy, dt. blue 3250 4250 Shale, calcareous, sandy, dt. blue 4350 4350 Shale, calcareous, sandy, dt. blue 4350 4600 Shale, very sandy, blue 4450 4850 Shale, very sandy, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue, shale, calcareous, blue, shale, calcareous, black 4850 4855 Shale, sandy 5323 5333 Sand, gray 5333 5343 Sand, gray 5333 5343 Sand, gray 5352 Shale, sandy, gra	Shale, sandy gra						
Shale, blue 1370 1460 Shale, hard 1460 1462 Shale, blue 1500 1580 Shale, sandy, blue 1500 1580 Shale, blue 1580 1680 Shale, blue 1710 1740 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, sandy, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4600 4650 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, sandy, very calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373	Shale, blue		•				
Shell, hard 1460 1462 1500 Shale, blue 1580 1680 Shale, sandy, blue 1580 1680 Sand, fine, gray - 7 bbls. water per hour 1680 1710 Shale, sandy blue 1710 1740 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Sond, gray 5333 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373 Shale, sandy, gray 5355 5373 Shale, sandy, gray 5355 5373 Shale, sandy, gray 5352 5373	chale, gray	•			*		
Shale, blue 1462 1500 Shale, sandy, blue 1500 1580 Shale, blue 1580 1680 Sand, fine, gray - 7 bbls. water per hour 1680 1710 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, blue 4350 4600 Shale, very sandy, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little cil Shale, calcareous, blue Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 K.	Shale, blue				•	•	·
Shale, sandy, blue 1500 1580 1680 Shale, blue 1580 1680 1680 1680 1680 1680 1680 1680 16	Sholo blue	· · · · · · · · · · · · · · · · · · ·					
Shale, blue 1580 1680 1680 Sand, fine, gray - 7 bbls. water per hour 1680 1710 1740 Shale, sandy blue 1710 1740 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, blue 3050 3250 Shale, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4600 4640 Shale, sandy, very calcareous, black 4650 4855 Shale, sandy 5323 5333 Shale, sandy 5323 5333 Shale, sandy 5323 5343 Coal, show of gas 5343 5349 Shale, sandy 5752 Shale					9		,
Sand, fine, gray - 7 bbls. water per hour 1680 1710 Shale, sandy blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 1910 3050 Shale, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, blue 4350 4600 Shale, calcareous, blue 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, sandy 5323 5333 Shale, sandy 5325 5373 Shale, sandy, gray 5333 5343 Coal, show of gas 5343 5349 Shale, sandy, gray 5352 5373	Shale blue		,				
bbls. water per hour 1680 1710 Shale, sandy blue 1710 1740 Shale, blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, blue 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.			1000				
Shale, sandy blue 1710 1740 Shale, blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, sandy, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue Shale, sandy 5323 5333 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell, sandy, gray 5352 5373 Shale, sandy, gray 5352 5373	bbls. water ne	r hour 1680	1710				
Shale, blue 1740 1875 Sand, dark 1875 1880 Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, calcareous, sandy, blue 4640 4850 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	Shale, sandy blu	le 1710					
Sand, dark Shale, sandy, gray Shale, sandy, blue Shale, blue Shale, blue Shale, calcareous, Slightly sandy blue Shale, calcareous, sandy, dk. blue, shell Shale, calcareous, sandy, dk. blue, shell Shale, calcareous, sandy, blue 4350 Shale, very sandy, blue 4350 Shale, very sandy, blue Shale, very sandy, blue Shale, calcareous, blue 4640 Shale, sandy, very calcareous, black 4850 Chloroform test showed little oil Shale, calcareous, blue Shale, sandy Shale, sa	Shale, blue		A Company of the Comp	De la companya di santa di sa			
Shale, sandy, gray 1880 1910 Shale, sandy, blue 1910 3050 Shale, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, blue 4350 4600 Shale, very sandy, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shele, sandy, gray 5352 5373 Sand - Approx. 2 M.			4 a	1.00	e de la companya de l	• • •	
Shale, sandy, blue 1910 3050 Shale, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue Shale, sandy 5323 5333 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.							
Shale, blue 3050 3250 Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	Shale, sandy, bl	ue 1910					
Shale, calcareous, slightly sandy blue 3250 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	Shale, blue	3050				•	
slightly sandy blue 3250, 4250 Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.						•	
Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	slightly sandy			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
Shale, calcareous, sandy, dk. blue, shell 4250 4350 Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	•	3250	4250				. •
Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.			Andrew Commencer	**		et un un	. •
Shale, calcareous, sandy, blue 4350 4600 Shale, very sandy, black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.					****		
blue			4350	1.0	en de la companya de La companya de la co		
Shale, very sandy,	phale, calcareou					The second of the second	
black 4600 4640 Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.		4350	4600				
Shale, calcareous, blue 4640 4850 Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	phate, very sand		40.0				
blue	1		4640				
Shale, sandy, very calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.		•	4050				4
calcareous, black 4850 4855 Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.			4850				
Chloroform test showed little oil Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	Calcaracia hi	ack voec	/OFE				**
Shale, calcareous, blue 4855 5323 Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	Chloroform test	UCOF AUDIN			•		
Shale, sandy 5323 5333 Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.		erfd .eu	r Chille	And the second	•		
Sand, gray 5333 5343 Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.		4855					
Coal, show of gas 5343 5349 Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.						•	
Shell 5349 5352 Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.	Sand, gray						
Shale, sandy, gray 5352 5373 Sand - Approx. 2 M.							
Sand - Approx. 2 M.	•						
			5373				
cu. it. gas 5575 5575							
	cu. ft. gas	5373	5375				
				1.			
				1			

From: R. G. Myers

Rock Springs, Wyoming

To:

S. J. Fisher

January 23, 1963

Gas Analysis Report
R. D. Murphy Well No. 1,
Clay Basin Field

Unit #1

Attached for your information and files is a copy of a gas analysis report on a sample of gas obtained from the above-captioned well.

RGM/ag

Attachment

cc: S. J. Fisher (3)

G. D. Baston P. E. Files

REPORT OF ANALYSIS

State Utah	F.S. No. 8793
County Daggett	
Well Owner Mountain Fuel Supply Company	
Location: Sec. 22 T. 3N R. 24E	Dace Completed Unknown April 1927
Open Flow MCF/D 3276	Wellhead Pressure p.s.i.g. 1,722
Producting Stratums	
Depth to (feet): 5,344	Thickness (feet): 5,344 o- 5,445
Stratigraphic Position of Producing Formation	Frontier
Sampled: Date: 11-28-62	
Mass Spectrometer Run No. 8948	Date of Run 1-3-63
Analysis:	
Methane 92.2 % Normal Pentane	0.1 % Oxygen Trace %
•	0.2 % Argon 0.0 %
	0.1 % Helium 0.029 %
	0.1 % Hydrogen Trace %
•	0.5 % H ₂ S 0.0 %
	co ₂ 0.1 %
Catculated gross B. t. u./cu. ft., dry at 60°F.	and 30 mercury 1,097 Total
CHECK OF DATA: The well data are accurate: () Without correction	(X) As corrected above
PERMISSION FOR PUBLICATION: Permission is hereby granted for the Bureau together with similar data released by other open analyses of gases from various fields, state.	arators, as part of a series of papers
	mpany
#	· · · · · · · · · · · · · · · · · · ·
Rev. 7-13-49	AND THE REAL PROPERTY AND THE PROPERTY OF THE

DEPARTMENT OF THE INTERIOR

Geological Survey Laboratory - Midwest, Wyoming

INCOMPTON TO BE PERCHAND RITH FACT ON IT. IN DAR

Warks on container	(Filler by Themal
Field Clay Pasin, Utah	Farm of Longo S.L. C. Oldo 31-A
Operator	(Serial lumber) Operator's Address Casper Typesing
Well to . Pott . it Aventy . 1/1 rec 21	73.4 R 21, E
Mample taken by	terresse Entertains
	r which bein sam in a droduced Paketa
septh to top of sand	··· Touth to therem i send ··········
is the well driller	ေနေရ အလူရာလည္း ကိုလုံးသူတို့ ျပည္သန္းစစ္စစ္စစ္သည့္သည့္ မေနေနေနေန မေနေနနဲ႔ မေနနဲ႔ မေန
	estro jourdisit
RETHOL F SALVELON	
Fleese place where carrie has obtained (a.	op hole, lead line, they tank, baller, etc.)
\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	*****
Method of production filesing, pumping, at	Ex Property of a common and a c
Enitial Productions	Present Productions
Formula oil	barrels (the second sec
(1) Neura reference	
Cherwise sample will be the manner	or he a sector with a figure uncommenced to be so associated to each social conversion; The no refer seal or thankly corbustions and the self all samples so tout there will

GAS AWALYE IS

Condition of sam	ple baboratory so
Analysis by	J. J. Crawford at Medwest, Wouling Lete . 5-16-35
	OREAT ANALYEIS
	Carbon dioxide (Sug) C.CA
	ియాగ్రామణ్ స్టర్ల్స్
	Meshane (CB
	Cunano (Colle) and the hor 13.17
	Mitropen (Rp) by difference 18.29
	Specific Gravity (Calculated)
	Specific Stavity (Coserved)085
	Calculated Gross 1 C. per ou. 15. at 60% a. And 15.025 lbs. cer sq. inco preceded 900
	HYD WALL STOR . FYEL TO THE RESERVE
	Trains of hydrogen bull ide for 100 co. et. of the . et. of
	in reality of byenn, in suto to so the following for the sections.
	Burgation of the American Section (Section 1997)
	for an coff of and if high like, for against, pressure as deter-
	were and the land

emarks and considerates;

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

305 Federal Building Casper, Wyoming

March 11, 1942

Mountain Fuel Supply Company,

Rock Springs, Wyoming.

Attention: Mr. B. W. Smedley.

Gentlemen:

Distillation of gasoline sample taken from the separator of the R. D. Murphy well No. 1, SW_{+}^{1} NW_{+}^{1} sec. 22, T. 3 N., R. 24 E., lease Salt Lake City 045051(a), Clay Basin field, Utah, gave the following results:

Sample from Frontier formation at 5373'

A.P.I. gravity at 60° F: 58.9 Barometer: 24.62 in.

OF

I. B. P. 113
10% over 165
50% over 234
90% over 356
E. P. 437

Recovery: 97%

Residue: 2%

Loss: 1%

Very truly yours,

DUNCAN,

Supervisor.

Gasoline sample from R.D. Murphy #1, etc.

Clay Basin

Salt Lake 045051

Mt. Fuel Supply Company

SW

Rock Springs, Wyo.

1

22

24 E

3N

xxxx S.L.B.&M.

2-21-42

Frontier

5373

separator

X

X



180 EAST FIRST SOUTH . P. O. BOX 11368 . SALT LAKE CITY, UTAH 84139 . PHONE (801) 534-5555

April 10, 1984

Working Interest Owners
Clay Basin Unit
Daggett County, Utah and
Sweetwater County, Wyoming

Gentlemen:

Mountain Fuel Supply Company, as designated operator of the Clay Basin Unit, hereby resigns as Unit Operator under the provisions of Section 4 of the Unit Agreement subject to: WEXPRO Company being designated successor Unit Operator by the committed working interest owners and approval by the Bureau of Land Management.

WEXPRO Company, a wholly owned second tier subsidiary company of Mountain Fuel Supply Company, has assumed all of the development and producing operations of Mountain Fuel. Office and operating personnel have been transferred to WEXPRO so there will be no physical change in operations.


MOUNTAIN FUEL SUPPLY COMPANY

BY:

W. F. Edwards Vice President

cc: Mr. E. W. Guynn
Chief, Branch of Fluid Minerals
Bureau of Land Management
136 East South Temple
University Club Building, 11th Floor
Salt Lake City, UT 84111

CLAY BASIN UNIT Daggett County, Utah



24E

UNIT OUTLINE (UTU63009X)

FRONTIER PA

11,162.43 ACRES

FRONTIER PA ALLOCATION FEDERAL 82.17194% STATE 9.63096% FEE 8.19710% 4,765.64 Acres



United States Department of the Interior

BUREAU OF LAND MANAGEMENT UTAH STATE OFFICE 136 E. SOUTH TEMPLE SALT LAKE CITY, UTAH 84111

April 26, 1984

WEXPRO Company P.O. Box 11368 Salt Lake City, Utah 84139

> Re: Successor Unit Operator Clay Basin Unit Daggett County, Utah and Sweetwater County, Wyoming

Gentlemen:

On April 26, 1984, we received an indenture dated April 10, 1984, whereby Mountain Fuel Supply Company resigned as Unit Operator and WEXPRO Company is accepted as Successor of Unit Operator for the Clay Basin Unit Agreement, Daggett County, Utah and Sweetwater County, Wyoming.

The indenture was executed by both parties. The signatory parties have complied with Section 6 of the unit agreement. The instrument is hereby accepted effective as of April 26, 1984. Please advise all interested parties of the change in unit operator.

Sincerely,

E. W. Guynn

Chief, Branch of Fluid Minerals

Enclosure



WEXPRO COMPANY LANDS & LEASING

Sec 22, 3N, 24E Chapley 15 June 88 Clay Busin U#1 emergency sit 42.382 1.00 SHEETS 5.50UARE NATIONAL MINISTRACTOR OF THE STATE OF THE tank with firewall delightrator. O weekhead. access

STATE OF UTAH DIVISION OF OIL, GAS AND MINING

1594 West North Temple, Suite 1210, PO Box 145801, Salt Lake City, UT 84114-5801

	_		
Page	1	of	5

MONTHLY OIL AND GAS PRODUCTION REPORT

OPERATOR NAME AND ADDRESS:			UTA	LH ACCOUNT NUMB	ER: N1070	
JOHN JOOSTEN WEXPRO COMPANY PO BOX 11070 SALT LAKE CITY UT 8414	47			ORT PERIOD (MONT	H/YEAR): 9 / 96 (Highlight Changes)	
			7.11	arbbb rear oreit (migmigm Changes)	
Well Name	Producing	Well	Days		Production Volumes	·
API Number Entity Location	Zone	Status	Oper	OIL(BBL)	GAS(MCF)	WATER(BBL)
BUG #4 · 4303730542 00995 36S 26E 16 BUG 17	DSCR					
4303730793 00995 36S 26E 16	DSCR					
4303730591 01010 36S 26E 22 BUG 14	DSCR					
4303730605 01020 36S 26E 17 BUG #15	DSCR					
4303730606 01020 36S 26E 17 BUG 16	DSCR					
73730607 01020 36S 26E 17 - 413	ISMY					
4303730610 01020 365 26E 17	DSCR					
4300915625 01025 03N 24E 22 CLAY BASIN UNIT 7	FRTR					
4300915631 01025 03N 24E 21	FRTR					<u> </u>
4300915632 01025 03N 24E 19 CLAY BASIN UNIT #9	FRTR					
4300915633 01025 03N 24E 15 CLAY BASIN UNIT 12	FRTR			!		
4300915636 01025 03N 24E 22 CLAY BASIN UNIT 13	FRTR					
4300915637 01025 03N 24E 21	FRTR					
		1	TOTALS			
OMMENTS:		-				
hereby certify that this report is true and complete to the	ne best of my	knowledge.		Da	ite:	
ame and Signature:					Felephone Number:	
2/93)				-		

* Division of Oil, Gas and Mining OPERATOR CHANGE WORKSHEET	Routing 6-IVEC
Attach all documentation received by the division regarding Initial each listed item when completed. Write N/A if item	is not applicable. 4-VLD 9-FILE 5-RJF
• • • • • • • • • • • • • • • • • • • •	esignation of Agent perator Name Change Only
The operator of the well(s) listed below has change	ged, effective: 4-26-84
TO: (new operator) WEXPRO COMPANY (address) PO BOX 11070 SALT LAKE CITY UT 84147 Phone:(801)530-2586 Account noN1070	FROM: (old operator) MOUNTAIN FUEL SUPPLY CO [(address) 180 E 100 S SALT LAKE CITY UT 84139 Phone: (801)534-5267 Account no. N0680
WELL(S) attach additional page if needed:	*CLAY BASIN UNIT
Name: **SEE ATTACHED** API: Name: API:	Entity: S T R Lease: Entity: S T R Lease:
OPERATOR CHANGE DOCUMENTATION N/4 1. (r649-8-10) Sundry or other legal documents.	mentation has been received from the FORMER operator
2. (r649-8-10) Sundry or other legal docume to this form). * see comments.	entation has been received from the NEW operator (Attach
any wells in Utah. Is the company register	ontacted if the new operator above is not currently operating ered with the state? (yes/no) If yes, show company
iviake note of blivi status in comments sec	NLY. The BLM has been contacted regarding this change. etion of this form. BLM approval of Federal and Indian well place prior to the division's approval, and before the
NA 5. Changes have been entered in the Oil and	Gas Information System (3270) for each well listed above.

NA 6. Cardex file has been updated for each well listed above. * See Comments.

Le 7. Well file labels have been updated for each well listed above. (11-6-96)

Changes have been included on the monthly "Operator, Address, and Account Changes" memo for distribution to Trust Lands, Sovereign Lands, UGS, Tax Commission, etc. * See Comments.

A folder has been set up for the Operator Change file, and a copy of this page has been placed there for reference during routing and processing of the original documents.



Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. LEASE DESIGNATION AND SERIAL NO. SEE ATTACHED SHEET

SUNDRY NOTICES AND I	DEDODTE ON WELL O		SEE ATTACHED SHEET
Do not use this form for proposals to drill as to door	NEPORIS ON WELLS		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
Do not use this form for proposals to drill or to deep	en or reentry to a different reservoir.		
Use "APPLICATION FOR PERMIT -"	for such proposals		NA
			7. IF UNIT OR CA, AGREEMENT DESIGNATION
SUBMIT IN TRIP	LICATE		CLAY BASIN
1. TYPE OF WELL			UNIT AGREEMENT # 892000323B
OIL GAS WELL X WELL OTHER			8. WELL NAME AND NO.
- Contract Contract			
2. NAME OF OPERATOR WEXPRO COMPANY			SEE ATTACHED SHEET
3. ADDRESS AND TELEPHONE NO.			9. API WELL NO.
P. O. BOX 458, ROCK SPRINGS, WY 8290	2 (207) 202 0701	•	SEE ATTACHED SHEET
			10. FIELD AND POOL, OR EXPLORATORY AREA
4. LOCATION OF WELL (FOOTAGE, SEC., T., R., M., OR SURVEY DES	SCRIPTION)	1	CLAY BASIN
CDE ACCE ACCES	•	A Add	11. COUNTY OR PARISH, STATE
SEE ATTACHED SHEET		2 Establish	
		2	DAGGET COUNTY UTAH
12. CHECK APPROPRIATE BOX(S)	O INDICATE NATURE OF N	2-202	
TYPE OF SUBMISSION		Copy for la well on back of Sundy	ER DATA
Notice of Intent	Abandonment	- Copy for	
	Recompletion	of our	Change in Plans
X Subsequent Report	<u></u>	wer a wa	New Construction
	Plugging Back	Dade & Sundy	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair	Nacy 1	Water Shut-Off
- The state of the	Altering Casing	<u></u>	Conversion to Injection
	X Other VARIANCE		Dispose Water
		(Note:	Report results of multiple completion on Well
Describe Proposed or Completed Operations (Clearly state all pertinent subsurface locations and measured and true vertical doubte for all personal subsurface locations.)	details, and give pertinent dates, including actions		
subsurface locations and measured and true vertical depths for all ma	irkers and zones pertinent to this work 1*	o date of starting any proposed work. If	well is directionally drilled, give

Wexpro Company is requesting a variance from the requirement to install Enardo vent stack valves on the storage tanks for the wells listed on the attached sheet. This request is due to the potential freezing problems encountered with the Enardo vent stack valves. In the past storage tanks have been over pressured, as they could not vent, and once over pressured ruptured causing the top of the tank to be thrown from the tank. The potential tank damage, loss of fluids, fire and ground contamination are our primary safety and environmental concerns for this request.

RECEIVED

OCT 2 8 2002

DIVISION OF OIL, GAS AND MINING

Accepted by the Utah Division Oil, Gas and

Federal Approval Of This Action Is Necessary

14.	I hereby certify that the foregoing is true.
Sian	

__ fille__ Title G. T. Nimmo, Operations Manager

October 21, 2002

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title 18 U.S. C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

UNIT NO. 62

SL-045051-b

WELL NAME	API NUMBER	LEGAL DESCRIPTION	COUNTY, STATE	UNIT CA PA NUMBER	LEASE NUMBER
CLAY BASIN FIEL	D_UNIT_			892000323B	
UNIT NO. 1	ACCOUNTS:	SW NW 22-3N-24E	DAGGETT, UT		SL-045051 - a
UNIT NO. 7	4300915631	SE SW 21-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 8	4300915632	NE NE 19-3N-24E	DAGGETT, UT		SL-062508
UNIT NO. 9	4300915633	NE SW 15-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 12	4300915636	NW SE 22-3N-24E	DAGGETT, UT		SL-045051-a
UNIT NO. 13	4300915637	SE NW 21-3N-24E	DAGGETT, UT		SL-045051-a
UNIT NO. 14	4300915638	NW SW 20-3N-24E	DAGGETT, UT		SL-062508
UNIT NO. 15	4300915639	SE SW 23-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 16	4300930003	SW NW 25-3N-24E	DAGGETT, UT		SL-045049
UNIT NO. 17	4300930004	NW NE 27-3N-24E	DAGGETT, UT		SL-045053-a
UNIT NO. 18	4300930006	NW NW 23-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 19	4300930008	SE SE 17-3N-24E	DAGGETT, UT		SL-045051-b
UNIT NO. 20	4300930007	NW NW 22-3N-24E	DAGGETT, UT		SL-045051-a
UNIT NO. 22	4300930001	NW SE 16-3N-24E	DAGGETT, UT		ML-807
UNIT NO. 23	4300930009	SE NW 26-3N-24E	DAGGETT, UT		SL-045053-b
UNIT NO. 61	4300930060	NE SE 20-3N-24E	DAGGETT, UT		SL-045051-b
	100000000				OI 045054 h

SE SE 21-3N-24E

4300930061

DAGGETT, UT

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135

	Expires:	Marci	1 31, 18	93
LEASE	DESIGNATION	AND !	SERIAL	NC

		SL-0454051-a
SUNDRY NOTICES AND RI Do not use this form for proposals to drill or to deeper Use "APPLICATION FOR PERMIT -" for	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUBMIT IN TRIPL	CATE	7. IF UNIT OR CA, AGREEMENT DESIGNATION
1. TYPE OF WELL		CLAY BASIN
OIL GAS WELL X WELL OTHER		8. WELL NAME AND NO.
2. NAME OF OPERATOR		CLAY BASIN UNIT 1
Wexpro Company		9. API WELL NO.
3. ADDRESS AND TELEPHONE NO.	(227) 222 2724	43-009-15625
P. O. Box 458, Rock Springs, WY 82902	(307) 382-9791	10. FIELD AND POOL, OR EXPLORATORY AREA
4. LOCATION OF WELL (FOOTAGE, SEC., T., R., M., OR SURVEY DESC	CRIPTION)	CLAY BASIN - FRONTIER
2069' FNL, 265' FWL SW NW 22-3N-24	JE	11. COUNTY OR PARISH, STATE DAGGETT, UTAH
CHECK APPROPRIATE BOX(S) T	O INDICATE NATURE OF NOTICE, REPORT, OF	OTHER DATA
TYPE OF SUBMISSION	TYPE OF A	CTION
X Notice of Intent	Abandonment	Change in Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Cleanout and replace wellhead	Dispose Water
		(Note: Report resurts of multiple completion on Well Completion or Recompletion Report and Log form.)
 Describe Proposed or Completed Operations (Clearly state all pertinent 	details, and give pertinent dates, including estimated date of starting any propo-	sed work. If well is directionally drilled, give

subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Wexpro Company plans to workover this well in 2006 in order to restore it to productive status. The specific timing of the work in 2006 will be dependent upon equipment and manpower availability.

The following is a general description of the work proposed.

- 1. MIRU a workover rig and associated equipment.
- 2. Blow the well down and pump kill fluid. Remove the upper wellhead and install 6", 5M BOPE.
- 3. Attempt to pull the tubing. If the tubing is stuck it will be cutoff and washed over to recover.
- 4. The well will then be cleaned out with an air foam unit and new tubing will be run in and landed.
- 5. BOPE will be removed and new wellhead equipment installed.

RECEIVED

CONSENT TO CPERATOR Side: 11-3-05 Initials: CHO		OCT 1 / 2005 DIV. OF OIL, GAS & MINING
14. I hereby certify that the foregoing is true and correct Signed Signed	Director, Technical Services	Date 10 · 7 · 5
(This space for Federal or State office (se) Approved by Conditions of approval, if any:	Accepted by the Utah Division of Oil, Gas and Mir	Federal Approval Of This Action is Necessary
Title 18 U.S. C. Section 1001, makes it a crime for any person knowingly an representations as to any matter within its jurisdiction.	d willfully to make to any department or agency of the United states and take to Bate: *See Instruction on Reverse Side \$1.	ctitious or traudulent statements or

Form 3160-5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004- 0137

	BUREAU OF LAND M.	ANAGEMENT		Expi	ires: March 31, 2007
CITA	IDDV NOTICES AND DE	DODTE ON XX		5. Lease Serial No.	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					SL-045051-a e, or Tribe Name
				7 1611-2 04 4	1/ N
	IPLICATE - Other Instructio	ns on reverse s	ide.	Clay Basin	greement Name and/or No.
1. Type of Well Oil Well X Gas Well	Other			8. Well Name and 1	
				4	
2. Name of Operator				Clay Basin U	Jnit No. 1
WEXPRO COMPANY		In 191 32 6 1		9. API Well No.	
3a. Address P. B. BOX 458		3b. Phone No. (inch	ide area code)	1	2 000 15625
ROCK SPRINGS, WY 82902		(307)3	82-9791	10. Field and Pool,	or Exploratory Area
4. Location of Well (Footage, Sec., T.	, R., M., or Survey Description)	Lat.		_	Basin - Frontier
2069	265			11. County or Parish	
SW NW FNL	FWL 22 T 3N R 24	4E Long.		Daggett	
12. CHECK APPROF	RIATE BOX(S) TO INDICAT	E NATURE OF	NOTICE REPO		
	turite box(s) to inbierti			KI, OK OTILKI	<i>)</i> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
TYPE OF SUBMISSION	,	17	PE OF ACTION		
X Notice of Intent	Acidize	Deepen	Production (Start/ Resume)	Water Shut-off
	Alterias Cosins]	Dr. J	Ē	=
	Altering Casing	Fracture Treat	Reclamation	L	Well Integrity
Subsequent Report	Casing Repair	New Construction	Recomplete	L	Other
·	Change Plans X	Plug and abandon	Temporarily .	Abandon	
·		, 1		-	
Final Abandonment Notice 13. Describe Proposed or Completed	Convert to Injection	Plug back	Water Dispos		en e
following completion of the involvesting has been completed. Final determined that the site is ready for Wexpro intends to plug and December 31, 2007. Set rig anchors and dig a flat off the existing wellhead an P&LD the production tubin Spot a 500' balanced cement balanced plug to a maximum Tag the plug and POOH. Posacks] from 2500' - 3000'. Funtil 5 bbls of displacement Tag the plug and POOH. Ex "One-inch" a 60' top out plug Install a regulation dry hole Final surface reclamation w	are pit. MIRU workover rig. Bl. d strip on and weld on an 11", g. TIH with 2-3/8" workstring at plug [approximately 35 sacks on of 1500 psig or until 5 bbls is erforate from 2945-2950', 6 sp. POOH with 750' of tubing and it is achieved. Leave final display accavate around the wellhead and g inside the 4-1/2" casing. "Or marker and backfill to GL. RD till be completed as soon as we	on in a multiple compleonly after all requires to the following property of the well down 5M x 8-5/8" casing to +/- 5325'. The square of the case of t	etion or recompletion ments, including reclarations, including reclarations, including reclarations, including reclarations, and pump kill flang head equipped as 750' of tubing a final displacement of spot a 500' balaure up on the balaure up on the balaure up on the well overning strings as necest plugs in the casual other equipmental of the requipmental tow.	in a new interval, a amantion, have been or intent to complet the land. Unland the to land and reverse out. It ent pressure on the anced cement plug anced plug to a manight.	Form 3160-4 shall be filed once completed, and the operator has the this work before the shing and cut off and strip PE. Pressure up on the ewell overnight. g [approximately 35 aximum of 1500 psig or ximately 3 feet below GL. ve been exposed.
	Bellby			Completion Mana	iger
Signature /////	51/	Date	12/5	/ 57	
U	THIS SPACE FOR F	EDERAL OR ST	TATE OFFICE	ØSE	
Approved by		Title Uta	h Division	oin g Date	Federal Approval Of This Action Is Necessary
Approved by Conditions of approval, if any are attack certify that the applicant holds legal or which would entitle the app	ned. Approval of this notice does not vequitable title to those rights in the sub- licant to conduct operations	iject lease Office 3	211910	7-1	ACTION 15 HOUSE
Title 18 U.S.C. Section 1001 AND Tit States any false, fictitious or fraudulent st	ie 45 0.5.C. Section 1212, make n a	critical trial sails bereaf	A MAIN WATER A MAIN	fully to make any dep	artment or agency of the United
(Instructions on page 2)	or representations as to any me	E211'	TELLY		

RECEIVED

DEC 17 2007

Form 3160- 5	011111111111111111111111111111111111111					FORM APPROVED	
April 2004)	DEPARTMENT OF TH	MINING OMB No. 1004- 0137					
	BUREAU OF LAND MA	NAGEMENT	·	Expires: March 31, 2007			
				5. Lease Serial No.			
	DRY NOTICES AND RE			SL-045051-a			
Do no	ot use this form for proposals	to drill or to re-e	enter an	6. If Indian, Allottee, or Tribe Name			
	oned well. Use Form 3160-3 (A			7. If Unit or CA.	A arragment Nam	e and/or No	
	IPLICATE - Other Instruction	ns on reverse si	de.	Clay Ba	_	e and or 110.	
Type of Well							
Oil Well X Gas Well	Other			8. Well Name and No.			
2. Name of Operator	Name of Operator				n Unit	No. 1	
WEXPRO COMPANY				9. API Well No.			
3a. Address		3b. Phone No. (inch	ide area code)		42 000 156	\c	
P. B. BOX 458		(307)3	82-9791		43-009-1562		
ROCK SPRINGS, WY 82902		`		10. Field and Po	-		
4. Location of Well (Footage, Sec., T	, R., M., or Survey Description)	Lat.			ay Basin - Fro	ontier	
SW NW 2069	265 22 T 3N R 24	4E Long.	•	11. County or P		T Y4. 1.	
FNL	FWL			Dagg		Utah	
12. CHECK APPROI	PRIATE BOX(S) TO INDICAT	E NATURE OF	NOTICE, REPOR	RT, OR OTHE	R DATA		
TYPE OF SUBMISSION			PE OF ACTION				
TITE OF SUBMISSION		1				. «	
X Notice of Intent	Acidize	Deepen	Production (S	tart/ Resume)	Water SI	nut-orr	
	Altering Casing	Fracture Treat	Reclamation		Well Inte	egrity	
		, 1	D		X Other		
Subsequent Report	Casing Repair	New Construction	Recomplete		2x Joulet		
	Change Plans	Plug and abandon	Temporarily A	Abandon	Request exter	nsion of time to	
Final Abandonment Notice	Convert to Injection Operation (clearly state all pertinent of	Plug back	Water Dispos		P&A well		
testing has been completed. Find determined that the site is ready for Wexpro Company respects conditions combined with until July 1, 2008 to computer Verbal approval for this reundersigned after an onsite Johnny Bowen and Wexpression of the site	fully requests an extension of tire the condition of the location its	only after all requirements be granted to elf are the reason softhe Vernal Bon conditions on twas noted during Acceptate Utah Div Oil, Gas at 21/810	complete the P&A is for the requested LM office in a foll 12/11/07. Present is ion of a manner of the chairs as we are in the chairs.	a of Clay Basing time extension low-up phone at the onsite value that the slight	on Unit No. 1. on. Wexpro as conversation were BLM rep th wellhead le	Winter weather sks to be given with the presentative, eak that had	
14. I hereby certify that the foregoing	is true and correct.						
Name (Printed/Typed) C.	A. Beilby	Title		Completion N	Manager		
Signature / 1/2 - 13 - 07							
- (Non)	THIS SPACE FOR I	FEDERAL OR S	STATE OFFICE				
	THIS OF AGE FOR						
Approved by		Title]	Date		
Conditions of approval, if any are att certify that the applicant holds legal of	ached. Approval of this notice does not or equitable title to those rights in the su	ubject lease Office					
Ten. 19 ILCC Section 1001 AND	pplicant to conduct operations Title 43 U.S.C. Section 1212, make it	a crime for any pers	son knowingly and wi	lfully to make an	y department or	agency of the United	
States any false, fictitious or fraudulen	t statements or representations as to any r	natter within its jurisd	iction.				
(Instructions on page 2)							



Form 3160- 5 (April 2004)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004- 0137

,	BUREAU OF LAND M	Expires: March 31, 2007			
CUMBBY NOTICES AND DEPORTS ON WELLS				5. Lease Serial No.	45054
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an				6. If Indian, Allottee, or	045051-a Tribe Name
abano	abandoned well. Use Form 3160-3 (APD) for such proposals.				
	IPLICATE - Other Instruction	ons on reverse si	de.	7. If Unit or CA. Agreer Clay Basin	nent Name and/or No.
1. Type of Well Oil Well X Gas Well	Other			8. Well Name and No.	
2. Name of Operator				Clay Basin Unit	No. 1
WEXPRO COMPANY				9. API Well No.	
3a. Address P. B. BOX 458		3b. Phone No. (inchu	de area code)	43-00	09-15625
ROCK SPRINGS, WY 82902		(307)38	32-9791	10. Field and Pool, or E	
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)	Lat.			in - Frontier
SW NW 2069 FNL	265 FWL 22 T 3N R 2	4E Long.		11. County or Parish, St Daggett	ate Utah
12. CHECK APPROI	PRIATE BOX(S) TO INDICA	TE NATURE OF 1	NOTICE, REPOR	T, OR OTHER DAT	ГА
TYPE OF SUBMISSION		TY	PE OF ACTION		
Notice of Intent	Acidize	Deepen	Production (St	tart/ Resume)	Water Shut-off
	Altering Casing	Fracture Treat	Reclamation		Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recomplete	一	Other
	Change Plans X	Plug and abandon	Temporarily A	بــــــ bandon	· · · · · · · · · · · · · · · · · · ·
Final Abandonment Notice	Convert to Injection	Plug back	Water Disposa		
13. Describe Proposed or Completed					pproximate duration thereof
Wexpro plugged and abance The daily reports of the oper This work was witnessed by	Il Abandonment Notice shall be filed final inspection.) Idoned Clay Basin Unit No.1 dueration are attached as well as a y Alan Walker of the Vernal Bivill be completed as soon as possible to the sound of the completed as soon as possible to the sound of the sound	aring the period of a wellbore diagram	7/07-22/08.	•	
14. I hereby certify that the foregoing is Name (Printed/ Typed) C. A. Signature	Strue and correct. Beilby THIS SPACE FOR F	Title Date FEDERAL OR ST	8-12-		
		<u> </u>		1	· · · · · · · · · · · · · · · · · · ·
Approved by Conditions of approval, if any are attac	hed. Approval of this notice does not	Title warrant or		Date	Tyme T
certify that the applicant holds legal or				<i>i</i> .	RECEIVE
Title 18 U.S.C. Section 1001 AND Ti States any false, fictitious or fraudulent s	itle 43 U.S.C. Section 1212, make it a	a crime for any person		lly to make any departm	
(Instructions on page 2)					•

CLAY BASIN NO. 1 P&A REPORTS

CLAY BASIN NO. 1

07/07/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: N/A. SICP: N/A. Traveled to CBU #175 f/ RS

Loaded out rigs equip. Roaded rig and equip from CBU #175 to Clay Basin #1. Spotted in rig to WH. Waited on rigs equip. Spotted in all equip and leveled rig on jacks. LD pump lines to WH. Winds too strong for RU. Spotted one 400 bbl upright tank and filled same w/fresh water. SDFD. Crew traveled. Scott Colvin

AFE: \$ Comp Daily Cost: \$17,168 Comp Cum: \$17,168

07/08/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 20 psig. SICP: 125 psig. Traveled. RU rig, installed a new valve on csg. HU to tbg and loaded hole w/60 bbls of fresh water before circ was est. Circ'd 2 hole vol w/160 bbls. Small to medium pieces of fm in return. Circ'd at 700# at 2 ¾ bpm. LD returned line to prod pit, attempted to break out valve on top of tbg. Tbg twisting in pack-off assy. CIWSDFD, Traveled. Took swedge into machine shop to have X-O manufactured For PU on string and WL operations. Scott Colvin

<u>AFE: \$ Comp Daily Cost: \$8,560</u> <u>Comp Cum: \$25,728</u>

07/09/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 20 psig. SICP: 125 psig. Traveled. Checked press, HU and pumped 5 bbls of water before circ was est, rolled hole w/150 bbls. RU WL, chemical cut -off 2-3/8" tbg. @ 30' from surface. POOH RD wireline. ND upper WH assy at 4" flange, LD upper WH assy. And 20-1/2' jt of 2-7/8" + 6' of 2-3/8" tbg., Cut 8-5/8" bell npl and installed npl into a 8-5/8" X 11", 3K csg head and welded up same. NU 4" flange and csg head and a 11", 3K X 7-1/16" 3K spool w/and 7-1/16" 5k BOPE. RU floor tongs and slips. Dug out from around WH to expose top 2 csg landing assy's while waiting on fishing tools and tbg. MU fishing OS dressed to catch 2-3/8" tbg. RIH w/fishing tool. Latched onto fish top @ 41' from surface. Worked tbg out of hole 30' pulling 25K over string wt. CIWSDFD. Waited on 2-3/8" EUE box X 2" 10 third pin X-O. Traveled. Note: 4" flanges below new csg head have a 4-1/8" ID, and the 4 ¾" OD prod csg has 4-3/16" ID. Scott Colvin

AFE: \$ Comp Daily Cost: \$14,668 Comp Cum: \$40,396

07/10/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 20 psig. SICP: 125 psig. Traveled. PU on tbg, worked tbg. Pulling 25K over string wt. Worked tbg up hole 12 more feet. EOT @ 5,363'. Tbg stuck. Could gain no further movement up hole. Called for free-point and back-off truck and tools. Waited on WL truck. RIH w/1 ¾" core bbl to make gauge run. Tools set down @ 5304' WLM. POOH LD tools. PU MU RIH w/free-point tools. Free pointed tbg @ 5297', 100% free. POOH LD free-point tools. PU 1-11/16" OD jet cutter, RIH and set down in tbg @ 5,304' WLM, PU 1' and cut tbg at 5,303' WLM. RD WL, POOH LD over-shot. POOH LD prod tbg. 173 JTS + 1-20' piece. CIWSDFD.

Traveled. Scott Colvin

AFE: \$ Comp Daily Cost: \$20,975 Comp Cum: \$61,371

07/11/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: neg. Traveled. Unloaded 176 of 2-3/8" N-80 workstring and rental tbg. Loaded out original prod string on truck. Pulled protectors and SLM work string, Re-leveled rig again. PU RIH w/notched collar and 171 jts of 2-3/8" work string to fish top at 5,285' KBM. LD 1jt EOT @ 5276.05' KBM. HU to tbg and circ'd hole w/90 bbls of fresh water. CIWSDFWE. Traveled. Note: Fish top found @ 5285.50' w/ workstring tbg, putting btm of original prod tbg. @ 5363.93' kbm. Fish top is 59.42' above OH, and EOT 18.98' into the open hole section. Scott Colvin

AFE: \$ Comp Daily Cost: \$10,537 Comp Cum: \$71,908

07/14/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: neg. Traveled. Spotted in Halliburton cementers and RU same. Press tested ines and est. Circ'd, sfty mtg. PLUG NO.1 Mixed 40 sks of neat "G" cmt to a 15.8# slurry and spotted cmt from 5276 up to 4714', POOH LD 20 jts of tbg. Reversed out cmt f/4665' w/30 bbls of fresh water. Closed in csg valve and applied 500psi surface press to cement. SI tbg. SDFD. Traveled. Scott Colvin

AFE: \$ Comp Daily Cost: \$6,355 Comp Cum: \$78,263

07/15/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: 0 psig. Traveled. PU single in w/ tbg. Tagged cement plug No. 1 @ 4,986.15' KBM. LD 1 jt and HU to circulate Circulated reverse w/ 35 bbls of fresh water, Returned 2 bbls un-set cement slurry to tank. Pumped 40 bbls of corrosion inhibited water w/ bioside and displaced same w/ 10 bbls of fresh water. Putting treated water from 4970' up to 2,600'. POOH LD tubing to 2600', POOH SB 42 stands of tbg in derrick. (2616') RU WL, RIH making 2 perforating runs w/ 3-1/8" select-fire, 60deg, phased perf. Guns. PLUG NO. 2 Perforated 4-3/4" casing w/ 4-spf from 2770-75, 2830-35, 2890-95, 2945-50'. 4-3/4" casing annulus went on a vacum after first perf run and equalized. Fluid level in 4-3/4" casing was @ 725' from surface on run #2. More vacum on casing after 2nd perf. Run. RD WL, install stripper head, PU MU MSCICR.. TIH w/ MSCICR(insalled stripper rubber after 5 stands in) to 2619', PU and set CICR @ 2617'. HU and tested tbg and retainer valve to 2000#, Sheared out of CICR, Stung back in and tested annulus to 500#, Estab. Injection rate at 3 bpm @ 0# psi. Note: Fluid level was at approx. 900' before psi tests and injection rate test. Mixed and pumped 175 sks of neat "G" cement at an average 16.2# slurry (36 bbls slurry and 20.8 bbls of mix water) at an average rate of 2 bpm and 38 #, with 2 bbls of cement and 9 bbls of displacement left to pump 6-1/4 X 4-3/4 annulus started to flow water at approx. 1/4 bpm.

Displaced cement w/ 8-1/2 bbls of water, Stung out of CICR. LD 2 jts. Reversed out from 2556' w/ 20 bbls of water, returned approx. 3/4 bbl of cement to surface. HU and displaced hole w/ 50 bbls of corrosion inhibited water w/ biocide Pulled stripper rubber and POOH LD tbg. CIWSDFD. Scott Colvin

AFE: \$ Comp Daily Cost: \$19,134 Comp Cum: \$97,397

07/16/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: 0 psig. Traveled. RD floor and equip., ND BOPE an spools down to 4" flange. RU power swivel, PU 1 3-1/8" drill collar and tbg. Subs w/ inside cutter. RIH tightened connections running to 41', made inside cut on 4-3/4" casing @ 39.5' from surface. POOH w/ cutter. RD power swivel, PU mu casing spear, POOH LD 39.5' of 4-3/4" casing and landing bowl assy. Pumped fluids to 400 bbl open top tank, RD pump and lines, Made ready for RD. Waited on WL. to perforate. RU WL. PU RIH w/ 1-4', 3-1/8" perf. Perforated casing strings from 118-120'w/8 holes 60 deg. phased. RD WL. RD rig and pulled guywires to road rig to Church Buttes field. Make ready for rig move. Road rig off location for excavation work around well head. SDFD Traveled. Scott Colvin

AFE: \$ Comp Daily Cost: \$21,137 Comp Cum: \$118,534

07/17/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: 0 psig. Traveled. Welded on a 5-1/2" X 2" swedge to inside of 6-3/4" casing. Dug up and exposed casing strings down to cellar bottom 15' below ground level. Traveled. Scott Colvin

AFE: \$ Comp Daily Cost: \$7287 Comp Cum: \$125,821

07/18/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: 0 psig. Traveled, rig and crew on stand-by. Cleaned and scraped dirt and rust from around csg string landings to expose annulus. RU Redi Services to hydro-blast/ clean off WH below ground level up to surface. Made arrangements for culvert ring and cmt for WH, SDFD, traveled.

Scott Colvin

AFE: \$ Comp Daily Cost: \$5,325 Comp Cum: \$131,146

07/21/08

Perfs: O.H. Completed f/ 5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: 0 psig. Traveled, rig and crew on stand-by.

Waited on culvert ring. Installed 8' dia X 10' long culvert ring over and around WH. Back filled around culvert ring and filled btm 2' w/4 yd of 6sk concrete. SDFD. Loaded out track hoe. Traveled. Scott Colvin

AFE: \$ Comp Daily Cost: \$10,689 Comp Cum: \$141,835

07/22/08

Perfs: O.H. Completed f/5,443' - 5,445'. Fm: Frontier. SITP: 0 psig. SICP: 0 psig. Traveled. RU Halliburton cementing services, sfty mtg and press tested lines. PLUG NO. 3 (TOP-PLUG) Mixed and pumped 530 sks of neat "G" cmt and pumped a total of 108 bbls of slurry at 15.8# ppg down 6-5/8" csg. String and filled 6-5/8 and 4 ¾" csg w/4 bbls cmt, cont'd to pump cmt slurry at 1.6 bpm @ an avg press of 270#. Had cmt returns to surface in 6-5/8" x 8 ¾" annulus after pumping 8 ½ bbls of cmt. Cmt returns up 8 ¾" X 10" annulus after 11 ½ bbls cmt pumped and returns up 12 ½ X 15 ½" annulus after pumping a total of 23 bbls cmt slurry. Cont'd to pump slurry and filled culvert to surface letting cmt fill remaining

annulus. Washed up pump and lines and waited on cmt 30 min. Cmt did not drop in culvert, Halliburton finished wash-up. RD cementers. Waited on welder, cut of pumping swedge. Topped of cmt inside of 6-5/8" csg annulus. Installed a regulation abandonment marker. Traveled. Note: Allen Walker w/BLM (Vernal) witnessed all cementing and plugging ops. Job complete, final report! Scott Colvin

AFE: \$ Comp Daily Cost: \$60,365 Comp Cum: \$202,200

Clay Basin Unit No. 1 Sec. 22 - 3N - 24E PLUG NO. 3 (top-out plug): 40' of **Dagget County, Utah** the 4-3/4" csg was cut and pulled Plugged and Abandoned 7-22-08 8'H x 10'W Culvert out of the well leaving 6-5/8" casing cab used as form to at surface. The 4-3/4" csg was perforated from 118-120' with 8 allow satisfactory surface plug holes. 530 sacks of neat G cement placement was pumped down the 6-5/8" and circulated to surface on the various casing annuli and allowed to fill an 8'W x 10'H culvert that had been placed around the excavated wellhead and thereby encasing the wellhead in cement. 20", 90# casing @ 105' no cementing record Circulation perfs from 118-120' - 8 15.5", 70# casing @ 896' no cementing record Estimated TOC behind 12-1/2" csg is 1450' 12.5", 50# casing @ 1851' cemented with 225 sx CICR @ 2617' PLUG NO. 2 is a 175 sack squeeze pumped below a 10", 45# casing @ 2830' cemented with 25 sx CICR @ 2617' thru squeeze perfs: 2770-75, 2830-35, 2890-95 and 2945-50. 8.25", 32# casing @ 4010' cemented with 25 sx 6.25", 26# casing @ 4710' cemented with ? Sx PLUG NO. 1 is a 40 sack balanced plug placed from 4714-5276'. Plugged tagged @ 4896'. 4-3/4", 16# casing @ 5344' cemented with 90 sx 2-3/8" tubing fish 5303-5363' KBM 3.25" Open hole section from 5344 to TD TD - 5445'

WEXPRO COMPANY E-BILL

Clay Basin Unit 1

Daggett County, Utah

Plug to Abandon Service 22-Jul-2008

Job Site Documents

SUMMIT Version: 7.20.130

Field Ticket

Field Ticket Number: 6027384	Field Ticket Date:	Tuesday, July 22, 2008
Ship To: Ship To: WEXPRO COMPANY E-BILL Clay Basin Unit, 1 343491 UNKNOWN,	Job Name: Order Type: Well Name: Company Code: Customer PO No.: Shipping Point: Sales Office: Well Type: Well Category:	PTA Streamline Order (ZOH) Clay Basin Unit 1 1100 = Rock Springs, WY, USA Rocky Mountains BD

Material	Description	QTY	UOM	Base Amt	Unit Amt	Gross Amount	Discount	Net Amount
7528	CMT PLUG TO ABANDON BOM	1	JOB	0.00	0.00	0.00		0.90
1	ZI-MILEAGE FROM NEAREST HES BASE,/UNIT Number of Units	220 2	MI	0.00	9.79	4,307.60	50%	2,153.80
2	MILEAGE FOR CEMENTING CREW,ZI Number of Units	220 5	MI	0.00	5.76	6,336.00	50%	3,168.00
16094	PLUG BACK/SPOT CEMENT OR MUD,ZI DEPTH	1 5344	EA	0.00	8,751.00	8,751.00	50%	4,375.50
	FEET/METERS (FT/M) Variants condition	1	FT					
16096	Plugging Back, EA ADD HR, ZI HOURS	1 9	EA	0.00	1,071.00	9,639.00	50%	4,819.50
139	ADC (AUTO DENSITY CTRL) SYS, /JOB,ZI NUMBER OF UNITS	1	JOB	0.00	2,275.00	2,275.00	50 %	1,137.50
132	PORT. DAS W/CEMWIN;ACQUIRE W/HES, ZI NUMBER OF DAYS	1 1	JOB	0.00	1,649.00	1,649.00	50 %	824.50
114	R/A DENSOMETER W/CHART RECORDER,/JOB,Z NUMBER OF UNITS	1	JOB	0.00	1,285.00	1,285.00	50%	642.50
14743	TUBING/ROTARY SUB RNTL,2.38",1ST DAY, ZI DAYS OR FRACTION (MIN1)	1 2	EA	98.10	32.70	130.80	50%	65.40
7	ENVIRONMENTAL SURCHARGE,/JOB,ZI	1	JOB	0.00	134.00	134.00		134.00
8	IRON SAFETY INSPECTION SURCHARGE /JOB ZI	1	ЈОВ	0.00	83.00	83.00		83.00
86955	ZI FUEL SURCHG-HEAVY TRKS >1 1/2 TON	220	МІ	0.00	0.57	250.80		250.80

Material	Description	QTY	UOM	Base Amt	Unit Amt	Gross Amount	Discount	Net Amount
material	Number of Units	2					5,5600111	-Net Amount
86954	ZI FUEL SURCHG-CARS/PICKUPS<1 1/2TON	220	м	0.00	0.19	209.00		209.00
	Number of Units	5						
372867	Cmt PSL - DOT Vehicle Charge, CMT	8	EΑ	0.00	241.00	1,928.00		1,928.00
432487	CMT, Bulk Cement Surcharge	1005	EA	0.00	1.38	1,386.90		1,386.90
87605	ZI FUEL SURCHG-CMT & CMT ADDITIVES NUMBER OF TONS	110 47.33	Mi	0.00	0.19	989.20		989.20
76400	ZI MILEAGE,CMT MTLS DEL/RET MIN NUMBER OF TONS	110 47.33	Mi	0.00	3.35	17,441.11	50%	8,720.55
3965	HANDLE&DUMP SVC CHRG, CMT&ADDITIVES,ZI NUMBER OF EACH	1008 1	CF	0.00	5.49	5,533.92	50%	2,766.96
92	PORTABLE RADIOS, ZI NUMBER OF JOBS	4 1	EA	0.00	323.00	1,292.00	50%	646.00
16114	BULK TRUCK, ON SITE,>6HRS,ZI HOURS OR FRACTION	1 19	EA	0.00	196.00	2,548.00	50%	1,274.00
100003685	CLASS G / PREMIUM	40	sĸ	0.00	43.48	1,739.20	50%	869.60
100003653	CFR-3	6	LB	0.00	14.69	88.14	50 %	44.07
100005050	HR-5	10	LB	0.00	11.07	110.70	50 %	55.35
100003685	CLASS G / PREMIUM	175	sĸ	0.00	43.48	7,609.00	50%	3,804.50
100003653	CFR-3	25	LB	0.00	14.69	367.25	50%	183.62
100005050	HR-5	33	LB	0.00	11.07	365.31	50%	182.65
100003685	CLASS G / PREMIUM	630	sĸ	0.00	43.48	27,392.40	50%	13,696.20
104535	ST SQUEEZE MANIFOLD, W/HES DAYS OR PARTIAL DAY(WHOLE NO.)	1 2	EA	0.00	626.00	1,252.00	50 %	626.00
Halliburton Rep:	KEVIN FOSTER			Totals	USD	105,093.33	50,056.23	55,037.10

Customer Agent: Halliburton Approval

Material	Description	0.77						
THIS OUTPUT DOES NO	T INCLUDE TAXES APPLICABLE CALL		UOM	Base Amt	Unit Amt	Gross Amount	Discount	Not Amount

THIS OUTPUT DOES NOT INCLUDE TAXES. APPLICABLE SALES TAX WILL BE BILLED ON THE FINAL INVOICE.
CUSTOMER HEREBY ACKNOWLEDGES RECEIPT OF THE MATERIALS AND SERVICES DESCRIBED ABOVE AND ON THE ATTACHED DOCUMENTS.

X Customer Signature	FIELD TICKET TOTAL: USD	55,037,10
Customer Information Only Agent		
Agent Userid		

Field Ticket Number: 6027384

Field Ticket Date: Tuesday, July 22, 2008

3 of 3

MALLEUSTUN

Cementing Job Summary

The Road to Excellence Starts with Safety Sold To #: 343491 Ship To #: UNKNOWN Quote #: Sales Order #: 6027384 Customer: WEXPRO COMPANY E-BILL Customer Rep: Well Name: Clay Basin Unit Well #: 1 API/UWI #: 43-009-15625 Field: City (SAP): UNKNOWN County/Parish: Daggett State: Utah Legal Description: Section 22 Township 3N Range 24E Contractor: Wexpro Rig/Platform Name/Num: Workover Job Purpose: Plug to Abandon Service Well Type: Development Well Job Type: Plug to Abandon Service Sales Person: VOLNER, THOMAS Srvc Supervisor: FOSTER, KEVIN MBU ID Emp #: 391223 Job Personnel HES Emp Name Exp Hrs Emp# **HES Emp Name** Exp Hrs Emp# **HES Emp Name** Exp Hrs Emp# BRITTEN, GLENN 370262 DENTON, J. 0 FOSTER, KEVIN Elliott 391223 JENSEN, SCOTT 5 450282 LUTHI, CHARLES 12 417697 MCKIE, SHAWN D 5 358960 Roger NGUYEN, L. 5 0 PAYZANT, GARY Fred 380528 **Equipment** HES Unit # Distance-1 way 10025113C 110 mile 10207304 110 mile 10248062C 110 mile 10322492C 110 mile 10417069 110 mile 10592954C 110 mile 10804551 110 mile 10825410 110 mile 10925853 110 mile 110 mile 10951237 10951242 110 mile 10998520 110 mile Job Hours On Location Date Operating Date On Location Operating Date On Location Operating Hours Hours Hours Hours Hours Hours TOTAL Total is the sum of each column separately Job **Job Times** Formation Name Date Time Time Zone Formation Depth (MD) Top Bottom Called Out 14 - Jul - 2008 04:00 MST Form Type **BHST** On Location 14 - Jul - 2008 06:30 MST Job depth MD 5344. ft Job Depth TVD 5344. ft Job Started 14 - Jul - 2008 08:55 MST Water Depth Wk Ht Above Floor Job Completed 22 - Jul - 2008 09:54 MST Perforation Depth (MD) From То Departed Loc 22 - Jul - 2008 11:55 MST **Well Data** Description New / Max ID Size Weight Thread Grade Top MD **Bottom** Bottom Top Used pressure lbm/ft in in MD ft TVD TVD psig ft ft ft Cement Plug 60 Cement Plug 2500. 3000. Cement Plua 4825 5325. Production 4.75 Unknow 4.082 16. 5344. 5344. Casing 2 3/8 Tubing Unknow 2.375 1.995 47 5325. 5325 n **Tools and Accessories** Type Size Qty Make Depth Qty Type Size Make Depth Type Size Qtv Make Guide Shoe Packer Top Plug Float Shoe Bridge Plug **Bottom Plug** Float Collar Retainer SSR plug set Insert Float Plug Container Stage Tool Centralizers **Miscellaneous Materials** Gelling Agt Conc Surfactant Conc Acid Type Conc % Qty Treatment Fld Conc Inhibitor Conc Sand Type Size Qty

Summit Version: 7 20 130

Cementing Job Summary

<u> </u>	nes/Diva #. 4		<u>ing salah di kabupatèn P</u>	luid Data			 		<u></u>	
Fluid	age/Plug #: 1 Stage Type	Fluid I	Name	Qty	Qty	Mixing	Yield	Mix Fluid		Total Mix
#					uom	Density Ibm/gal	ft3/sk	Gal/sk	bbl/min	Fluid Gal/s
1	Fresh Water			3.00	bbl	8.33	.0	.0	.0	
2	Mtn G	CMT - PREMIUM - C (100003685)			sacks	15.8	1.15	4.97		4.97
	94 lbm	CMT - PREMIUM - C	LASS G REG OR	TYPE V, BU	JLK (100	003685)				
	0.15 %	CFR-3, W/O DEFOAM		00003653)						
	0.25 %	HR-5, 50 LB SK (100	005050)			 :				
	4.969 Gal	FRESH WATER								
3	Fresh Water				bbl	8.33	.0	.0	.0	
SI	age/Plug #: 2									
Fluid #	Stage Type	Fluid	Qty	Qty uom	Mixing Density uom	Yield uom	Mix Fluid uom	Rate uom	Total Mix Fluid uom	
1	Fresh Water			10.0	bbl	8.33	.0	.0	.0	
2	Mtn G	CMT - PREMIUM - CI (100003685)	Ì	sacks	15.8	1.15	4.98		4.98	
	94 lbm	CMT - PREMIUM - CI	TYPE V, BU	JLK (100	003685)					
	0.15 %	CFR-3, W/O DEFOAM	MER, 50 LB SK (1	00003653)						
	4.98 Gal	FRESH WATER								
3	Fresh Water				bbl	8.33	.0	.0	.0	
St	age/Plug #: 3				. 1					
Fluid #	Stage Type	Fluid N	lame	Qty	Qty uom	Mixing Density uom	Yield uom	Mix Fluid uom	Rate uom	Total Mix Fluid uom
1	Fresh Water			00.5	bbl	8.33	.0	.0	.0	
2	Mtn G	CMT - PREMIUM - CI (100003685)	LASS G, 94 LB S	K 750	sacks	15.8	1.16	5.00		5.0
	94 lbm	CMT - PREMIUM - CI	ASS G REG OR	TYPE V, BU	JLK (100	003685)				
	5.019 Gal	FRESH WATER								
3	Fresh Water				bbl	8.33	.0	.0	.0	
	iculated Value	<u> </u>					olumes			
	ement	Shut In: Instant		Returns	_	Cement SI			Pad	
	Cement	- Land Control		ent Returns		Actual Displacement			Treatm	
	radient	15 Min	Spac	cers	1,,	Load and	вгеакоо	wn	Total J	lob
Rates	· · · · · · · · · · · · · · · · · · ·	A Givein au		Diantaga	ma a mé			A I.		
Circula	ang t Left In Pipe	Mixing Amount 0 ft Re	ason Shoe Joir	Displace	ment			Avg. Jo)D	
J e ![[e][ID Frac ring # 2		Frac Rin	-426	ID	1	Frac Ring #	10	ID
rac R	na #71a)	11) Frac min # /	ו נונו	rrac Rin	() # 3 (())	1 1777	1 12-	-180; KIIII #	4 (0)	

Summit Version: 7 20 130 Tuesday July 22 2008 11:39:00

HEALLING LIBITERS

Sales Person: VOLNER, THOMAS

Cementing Job Log

MBU ID Emp #: 391223

The Road to Excellence Starts with Safety

Sold To #: 343491	Ship To #: UNKNOV	VN Quote #:	Sales Order #: 6027384				
Customer: WEXPRO COM	IPANY E-BILL	Customer Rep:	Customer Rep:				
Well Name: Clay Basin Ur	nit We	H #: 1	API/UWI #: 43-009-15625				
Field:	City (SAP): UNKNOWN	County/Parish: Daggett	State: Utah				
Legal Description: Section	n 22 Township 3N Range	24E					
Lat: N 0 deg. OR N 0 deg.	0 min. 0 secs.	Long: E 0 deg. Ol	R E 0 deg. 0 min. 0 secs.				
Contractor: Wexpro	Rig/Platfo	rm Name/Num: Workover					
Job Purpose: Plug to Abar			Ticket Amount:				
Well Type: Development W	Vell Job Type:	Plug to Abandon Service					

Srvc Supervisor: FOSTER, KEVIN

Activity Description	Date/Time	Cht	Rate bbl/ min		ume bi	Pres	sure sig	Comments
		#		Stage	Total	Tubing	Casing	
Call Out	07/14/2008 03:00							
Pre-Convoy Safety Meeting	07/14/2008 05:00							
Crew Leave Yard	07/14/2008 05:15							
Arrive at Location from Service Center	07/14/2008 06:45							
Pre-Rig Up Safety Meeting	07/14/2008 07:00							
Rig-Up Equipment	07/14/2008 07:15							
Pre-Job Safety Meeting	07/14/2008 08:40							
Pressure Test	07/14/2008 08:46							
Pump Spacer	07/14/2008 08:48		3	3			150.0	PUMP 3 BBL H2O
Shutdown	07/14/2008 08:49							
Other	07/14/2008 08:51					-		BATCH UP CMT TO15.8 #
Pump Lead Cement	07/14/2008 08:59		3	8.2				PUMP 8.2 BBLS 40 SKS TYPE G CMY AT 15.8 PPG
Other	07/14/2008 09:02		·					FINISH CMT
Pump Displacement	07/14/2008 09:03		3	17.5			400.0	H2O
Other	07/14/2008 09:05							LOST INPUT TO OPTICEM
Shutdown	07/14/2008 09:09							
Other	07/14/2008 09:10							RIG PULL 20 JOINTS OF TUBING

Sold To #: 343491

Ship To #: UNKNOWN

Quote #:

Sales Order #:

6027384

SUMMIT Version:

7 20 130

Cementing Job Log

Activity Description	Date/Time	Cht	Rate bbl/		Volume bbl		sure sig	Comments	
열하시에 다시 그들의 병원다.		#	min	Stage	Total	Tubing	Casing		
Reverse Circ Well	07/14/2008 09:30		2	30			250.0	GOT 1BBL CMT BACK TO SURFACE AT 19 BBL OF H2O, AT 21 BBL OF H2O GOT CLEAR WATER BACK	
Start Squeeze	07/14/2008 09:32				Service Control of the Control of th			RIG CLOSED RAMS	
Pressure Up Annulus	07/14/2008 09:36		0.5				500.0	ATTEMPT SQUEEZE	
Shut In Well	07/14/2008 09:37				And the second s		500.0	RIG SHUT IN WELL LEAVE OVER NIGHT	
Post-Job Safety Meeting (Pre Rig-Down)	07/14/2008 09:50								
Rig-Down Equipment	07/14/2008 10:00								
End Job	07/14/2008 10:15								
Depart Location Safety Meeting	07/14/2008 11:30				480				
Depart Location for Service Center or Other Site	07/14/2008 11:40								
Depart Yard Safety Meeting	07/15/2008 05:15								
Crew Leave Yard	07/15/2008 05:45								
Arrive At Loc	07/15/2008 07:00								
Other	07/15/2008 07:15							TAGGED CEMENT @ 4985 FT, 295 FT ABOVE FISH	
Circulate Well	07/15/2008 07:30							CIRCULATE WELL WITH RIG	
Other	07/15/2008 07:45							WELL CLEAN	
Other	07/15/2008 08:10							BLM REQUESTED MORE CMT AS THEY INCREASED JOB SIZE. SENT BODY LOAD TO TOWN TO TAKE ON 50 SX	
Standby - Other - see comments	07/15/2008 08:20							RIG SET UP TO RUN WIRELINE AND SET RETAINER	
Other	07/15/2008 11:30							PERFERATE WELL @ 2770-75, 2830-35,2890,95, 2945-2950 ALL 4 SHOTS/FT	

Sold To #: 343491

Ship To #: UNKNOWN

Quote #:

Sales Order #:

6027384

SUMMIT Version:

7 20 130

Cementing Job Log

			Rate	Volume			sure	
Activity Description	Date/Time	Cht	bbl/ min	bbl		psig		Comments
보고하게 되는 일반 본다는 사람		#		Stage	Total	Tubing	Casing	
Set Packer	07/15/2008 12:30							MECHANICALLY SET RETAINER @ 2615FT
Pressure Test	07/15/2008 12:55		0.5	3		2000. 0		FILL TUBING AND TEST TO 2000 PSI
Pressure Up Annulus	07/15/2008 13:08		1	8			500.0	FILL ANNULAS AND TEST TO 500 PSI
Establish Rate	07/15/2008 13:11		2	2			.0	CONDUCT INJECTION TEST 2 BBL/MIN @ 0 PRESSURE, WELL DRINKING FLUID
Other	07/15/2008 13:16							WAIT ON VAC TRUCK
Pump Cement	07/15/2008 13:59		2	35.8		20.0		MIX AND PUMP CMT @ 15.8 PPG, 1.115 YIELD, 4.99 GPS, 175 SX MTN-G
Stop Pumping	07/15/2008 14:12							FINISH CEMENT
Pump Displacement	07/15/2008 14:16		2	9			20.0	
Stop Pumping	07/15/2008 14:20							UNSTING FROM RETAINER AND POOH 2 JOINTS TBG
Reverse Circ Well	07/15/2008 14:35		2	20			400.0	
Stop Pumping	07/15/2008 14:42					an Dident DR I va plant		TUBING CLEAN
Job Complete	07/15/2008 14:43							
Pre-Rig Down Safety Meeting	07/15/2008 14:55							
Rig-Down Equipment	07/15/2008 15:00							RIG DOWN AND WASH UP
Depart Location Safety Meeting	07/15/2008 16:00							
Crew Leave Location	07/15/2008 16:10							
Call Out	07/22/2008 03:00					CONTRACTOR	_	
Depart Yard Safety Meeting	07/22/2008 05:50					2.7700		
Crew Leave Yard	07/22/2008 06:00			_				
Arrive At Loc	07/22/2008 07:00							
Safety Meeting - Pre Rig-Up	07/22/2008 07:10							

Sold To #: 343491

Ship To #: UNKNOWN

Quote #:

Sales Order #:

6027384

SUMMIT Version:

7 20 130

Cementing Job Log

Activity Description	Date/Time	Cht	Rate bbl/ min	Volume bbl			sure sig	Comments
		#	123311	Stage	Total	Tubing	Casing	
Rig-Up Equipment	07/22/2008 07:20							
Safety Meeting - Pre Job	07/22/2008 08:25							
Pump Cement	07/22/2008 08:37	THE REAL PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY AND ADDRESS OF THE PROPERTY ADDRESS OF T	1.6	108	108		260.0	550 SKS MTN-G MIXED @ 15.8# 1.16Y 5.00G/SK
Returns To Surface	07/22/2008 08:47							
Cement Returns to Surface	07/22/2008 08:56							CMT TO SURFACE AND OVERFLOW TO OTHER ANNULUSES
Shutdown	07/22/2008 09:42							
Clean Lines	07/22/2008 09:48							
Shutdown	07/22/2008 09:54							
Other	07/22/2008 09:55							WAIT FOR DIRECTION FROM COMPANY MAN
Safety Meeting - Pre Rig- Down	07/22/2008 10:30	The second secon						
Rig-Down Equipment	07/22/2008 10:40							RIG DOWN AND WASH UP PUMP TRUCK TO EARTH PIT, LEFT 25 SKS CEMENT FOR CUSTOMER ON LOCATION
Depart Location Safety Meeting	07/22/2008 11:45							
Job Complete	07/22/2008 11:55							THANKS FROM HALLIBURTON CREWS

Sold To #: 343491


Ship To #: UNKNOWN

Quote #:

Sales Order #: 6027384

SUMMIT Version: 7 20 130

Rock Springs Cement



Customer:


Wexpro Well Description: P&A day1 Job Date: 14-Jul-2008 UWI:

Sales Order #: 6027384 Supervisor Foster

HALLIBURTON

OptiCem v6.1.1 14-Jul-08 10:21

Rock Springs Cement




Custo	omer:
XX7-11	D

WEXPRO Well Description: P&A

Job Date: 15-Jul-2008 UWI:

Sales Order #: 6027384

OptiCem v6.1.1 15-Jul-08 15:05



Customer:

WEXPRO

Well Description: CLAY BASIN UNIT #1

Job Date: 22-Jul-2008

Job Type: PTA SURFACE PLUG

Sales Order #: 6027384

Supervisor: S

SHAWN MCKIE

OptiCem v6.2.3 22-Jul-08 11:12

FORM 9

STATE OF UTAH
DEPARTMENT OF NATURAL RESOURCES

DIVISION OF OIL, GAS AND MINING	5. LEASE DESIGNATION AND SERIAL NUMBER: SL045051A		
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.	7. UNIT OF CA AGREEMENT NAME: CLAY BASIN		
1. TYPE OF WELL OIL WELL GAS WELL OTHER	8. WELL NAME and NUMBER: CLAY BASIN UNIT 1		
2. NAME OF OPERATOR: WEXPRO COMPANY	9. API NUMBER: 4300915625		
3. ADDRESS OF OPERATOR: PHONE NUMBER:	10. FIELD AND POOL, OR WILDCAT:		
PO BOX 458 CHY ROCK SPRINGS STATE WY 2/19 82902 (307) 382-9791	CLAY BASIN - FRONTIER		
FOOTAGES AT SURFACE: 2069 FNL, 265 FWL	COUNTY: DAGGETT		
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: SWNW 22 3N 24E	STATE: UTAH		
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA		
TYPE OF SUBMISSION TYPE OF ACTION			
NOTICE OF INTENT ACIDIZE DEEPEN DEEPEN	REPERFORATE CURRENT FORMATION		
(Submit in Duplicate) ALTER CASING FRACTURE TREAT Approximate date work will start: CASING REPAIR NEW CONSTRUCTION	SIDETRACK TO REPAIR WELL		
	TEMPORARILY ABANDON		
CHANGE TUBING PLUG AND ABANDON	TUBING REPAIR		
SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK	VENT OR FLARE		
(Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME)	WATER CHUT OF		
Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE	WATER SHUT-OFF		
CONVERT WELL TYPE RECOMPLETE - DIFFERENT FORMATION	OTHER:		
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volume			
This is to inform you that the workover previously proposed to cleanout the well and replace performed.			
NAME (PLEASE PRINT) CHRIS BEILBY TITLE COMPLETION M			
SIGNATURE DATE 8-20	-08		
This space for State use only)			

RECEIVED

AUG 2 0 2008